

# Index

## Numerics

8051 148  
8b/10b encoding 436–437

## A

A connector. See Standard-A connector  
abstract control model 172  
Access Denied 182  
ACK 47  
    PID 42  
    Setup packet 70  
ACK Transaction Packet 55  
    in bulk transfer 72–73  
    in control transfer 65  
    in isochronous transfer 83  
ACM driver 175  
ACPI 407  
active extension cable 454–455  
address  
    device 129  
    endpoint 110  
Address field 433  
Address state 93  
addressing triple 35  
A-device 472  
ADSL modem 169, 170  
Alcor Micro Corporation 182, 194  
alternate interface 108  
Am186CC 148  
AMD controllers 148  
    analyzer, protocol  
        hardware 410–412  
        software 412–413  
Andrew Pargeter & Associates 203  
ANSI INCITS 230-1994 436  
AnyHID 293  
AnywhereUSB 455  
API  
    defined 6  
    .NET and 243–252  
    Windows 212  
architecture, dual-bus 13  
ARM controller 148, 156  
arming (endpoint) 40  
ASIC device controller 138  
Asix Electronics Corporation 175  
Asynchronous transfer mode 169, 170  
AT command set 169, 172, 174  
AT2LP 188  
AT89C513x 148  
AT90USB1287 484  
AT90USBx 148  
AT91SAM7S 156  
AT91SAM7S/SAM9R64 148  
ATA/ATAPI 185  
ATM 169, 170, 172  
Atmel 148, 484  
Attached state 95  
attenuation 454  
AU9525 194  
audio class 165–169  
    INF file 239

## Index

Autoplay 189  
AVR 148  
AVR32UC3 148  
AWG (wire)  
    SuperSpeed 458, 461  
    USB 2.0 450, 451  
AX88172A 175

## B

B & B Electronics 465  
babble 383  
back voltage test 393  
balanced line 462  
bAlternateSetting 108  
bandwidth  
    bulk transfers 74  
    control transfers 68–69  
    interrupt transfers 78–79  
    isochronous transfers 84  
    use of 86  
battery charging 393–396  
battery-backed RAM 141  
battery-powered host 390  
BCD 100  
bcdDevice 102  
B-device 472  
bDeviceClass 102  
bDeviceProtocol 101  
bDeviceSubclass 101  
Belcarra Technologies Corporation 175  
bEndpointAddress 110  
binary device object store descriptor 114  
binary-coded decimal 100  
bInterfaceClass 108  
bInterfaceProtocol 110  
bInterfaceSubClass 110  
bInterval 112  
bit stuffing 430, 431  
Bitwise Systems, Inc. 145  
blittable 250  
Bluetooth 109  
bMaxBurst 57  
bMaxPacketSize0 101  
bMaxPower 104, 392

boot protocol 285  
BOS descriptor 114  
bRequest 119  
bridge cable 206  
broadcasting 8  
buffer  
    device 139  
    host 87  
    SuperSpeed hub 387  
buffer descriptor, PIC 149–151  
bulk transfer 71–75  
    purpose 37–38  
burst transaction  
    bulk and interrupt 57  
    isochronous 84  
bus  
    driver 215  
    length, maximum 455, 461  
    power 390–393  
    states (USB 2.0) 425–429  
bus speed. See speed

## C

C++ 244  
C161U 148  
C18 C compiler 152  
    descriptor 284–285  
    HID code 293  
    WinUSB and 349  
C8051F34x 145, 148  
cable  
    compatibility (USB 2.0/USB 3.0) 457  
    host-to-host 461  
    length (USB 3.0) 461  
    segment speed (USB 2.0) 440  
    shielding 464  
    USB 2.0 450–455  
capacitance, device 393  
capacitive load 454  
CAPI 172  
captive cable 452, 453–454  
catalog file 236, 423  
CBI protocol 184  
CBW 185

- CCID. See smart card
- CCS C compiler 152
- CDC. See communications device class
- cell phone 170
- ceramic resonator 139
- certificate store 423
- Certified USB logo 415, 419
- Certified Wireless USB 466
- characteristic impedance
  - full/high speed cable 451
  - SuperSpeed cable 458
- chip, USB. See interface chip, USB; microcontroller
- Chirp J and Chirp K 92-93, 428-429
- chkinf 240
- class code
  - device 101
  - interface 109
- class installer 241
- class key 229
- classes, USB
  - audio 165-169
  - communications device class 169-176
  - content security 176-177
  - device firmware upgrade 177-179
  - HID 180-182
  - IrDA 183-184
  - list of 165
  - mass storage 184-189
  - personal healthcare 189-190
  - printer 190-192
  - smart card 192-194
  - still image capture 194-197
  - test and measurement 197-198
  - video 198-202
- Clear Feature 127
- client driver 210, 213-215
- clock
  - accuracy 432-433
  - device 139
- CloseHandle 262, 265
- CLR (.NET) 212-213, 244
- Code Mercenaries 182
- ColdFire 175
- collection (HID) 287
  - in INF file 237
- COM port, virtual 160
  - See also communications device class
- Command Block Wrapper 185
- Command Status Wrapper 186
- communications device class 169-176
  - See also COM port, virtual
- compatible ID 237
- compiler
  - ARM 156
  - for Microchip chips 152
  - Keil (EZ-USB) 153
- compliance tests 415-419
  - back voltage 393
- composite device
  - CDC 171-172
  - defined 19
  - driver 214
  - installing 238
- compound device 19
  - bus power and 397
  - Suspend current 400
- configuration
  - assigning 94
  - getting and setting 132
- configuration descriptor 103-105
  - subordinate descriptors and 97
- Connect state 427
- connector
  - Powered-B 460
  - SuperSpeed 458-460
  - USB 2.0 451-453
- Container ID 388
  - device capability descriptor 115
- content security class 176-177
- control read transfer 62
  - SuperSpeed 65

## Index

- control transfer 61–71
  - abandoning 123
  - class request 136
  - Data stage 119–121
  - purpose 36
  - Setup stage 118–119
  - standard requests 124–135
  - Status stage 121–122
  - vendor request 136
- control write transfer 62
  - SuperSpeed 65
- CP2102 161
- CPU, device 140
  - See also microcontroller
- CRC 50
  - Data Packet Payload and 54
  - Error 330
  - field 434
- CreateFile 262–264
  - WinUSB and 350
- crystal oscillator 139
- CSM 176
- CSPLIT 380
- CSW 186
- current
  - bus. See bus power
  - inrush 398
- current source driver 445
- CWAV, Inc. 145
- CY7C638xx 182
- CY7C64713 148
- CY7C67200 EZ-OTG 483
- CY7C67300 EZ-HOST 483
- CY7C6801x 148, 153
- cyclic redundancy check. See CRC
- Cypress Semiconductor 188
  - controllers 148, 153, 182, 483
  - driver 144, 154
  - video applications 202
  - WirelessUSB 466
  - See also EZ-USB, specific chip
- CyUSB driver 154

## D

- Data field 434
- Data J and Data K 426
  - See also High-speed Data J and Data K
- data packet
  - bulk transfer 74
  - control transfer 68
  - interrupt transfer 77, 83
  - isochronous transfer 83
- Data Packet (SuperSpeed) 53, 54
  - Header 65
- Data Packet Payload 54
  - bulk transfer 74
  - control transfer 68
  - interrupt transfer 77, 83
- data phase 43
- data PID sequencing 53
- Data stage 62, 119–121
  - SuperSpeed 65
- data toggle 51–53
- DATA0, DATA1 42
  - See also data toggle
- DATA2 42, 52–53
- debug descriptor 115
- debugging
  - interface (Silicon Laboratories) 145
  - See also testing
- decorated name 235
- Default state 93
- deferred header packet 406
- deferred packet 55
- delay, inter-packet 434
- delayed packet 55
- descriptor
  - class- and vendor-specific 99
  - defined 97
  - HID 281–289
  - physical (HID) 314
  - report (HID) 286–289
  - standard 97–98
  - WinUSB 346
  - See also specific descriptor
- detachable cable 453
- DeVaSys Embedded Systems 145

- devcon example 220
  - development boards 144–146
  - devguid.h 219
  - device
    - address 129
    - class code 101
    - clock 139
    - defined 19
    - in PC 145–146
    - maximum number on bus 15
    - removing information about 241
    - requirements 142–143
    - simplifying development 142
    - steps in developing 24–26
    - See also firmware; interface chip, USB; microcontroller
  - device capability descriptor 114
  - Device Capacitance ECN 393
  - device change notification 265–275
  - device descriptor 99–102
  - device firmware upgrade class 177–179
  - device ID 236
  - device identification string 236–238
  - device installer 241
  - Device Instance ID 226
  - device interface GUID 219, 220
    - obtaining 252–254
  - device key 227
  - Device Manager 220, 223–226
    - Power Management 408
  - device notifications (Windows) 265–275
  - device object 211
  - device setup GUID 219–220
    - class key and 229
  - Device Simulation Framework 218
  - device\_qualifier descriptor 102–103
  - DEVICE\_REMOTE\_WAKEUP 127, 128
  - DeviceIoControl 212
  - devnode 255
  - DFU 177–179
  - Diagnostic device class 101
  - Differential 0/Differential 1 426
    - voltage 449
    - See also High-speed Differential 0/1
  - differential envelope detector 446
  - differential insertion loss 461
  - DIFx 241
  - Digi International 455
  - digital signature 238–239, 423–424
  - direct memory access 156
  - DirectInput 182
  - DirectMusic 169
  - DirectShow 202
  - DirectSound 169
  - DirectX 169, 182, 202
  - Dirid 232
  - disconnect detector (high speed) 446
  - Disconnect state 427
  - DLL
    - device and class installer 241
    - location 245
    - user-mode client driver 213
  - DllImport 247
  - DLP Design 469
  - DMA 156
  - DOS 9
  - double buffers 139
  - downstream 15
  - DP. See Data Packet (SuperSpeed)
  - DPP. See Data Packet Payload
  - driver
    - choosing 144
    - client 213–215
    - port 215
    - signed. See digital signature
    - writing 217–219
    - See also Windows driver
  - Driver Install Frameworks 241
  - driver key 231
  - Driver Test Manager 423
  - DSF 218
  - DTCP 176
  - DTM software 423
  - dual simplex 457
  - dual-bus architecture 13
- ## E
- ECM 169, 170, 172
    - driver 175

# Index

- ECN. See Engineering Change Notice
- edge rate 442, 464
- EEM 169, 170, 172
  - driver 175
- EEPROM
  - EZ-USB 153–155
  - in devices 140
- EHCI 216, 217
  - simulating 218
- EIA/TIA-232
  - compared to USB 3
  - See also RS-232
- Ellisys 411
- embedded host 471–485
- Embedded Hosts and/or Multiple Receptacles 452, 480–482
- encoding
  - SuperSpeed 436–437
  - USB 2.0 430–433
- End of Burst. See EOB
- End of Packet. See EOP
- End-of-High-speed-Packet 429
- endpoint
  - address 110
  - companion descriptor. See Superspeed endpoint companion descriptor
  - defined 34–35
  - descriptor 110–112
  - field 433
  - high bandwidth 78, 84
  - Status Change 383, 387
  - usages 111
- endpoint zero 34
- ENDPOINT\_HALT 127, 128
- Engineering Change Notice
  - Device Capacitance 393
  - Interface Association Descriptor 106
  - list of 14
  - Pull-up/pull-down resistors 444
  - Suspend Current Limit Changes 400
  - USB 2.0 Phase-locked SOFs 399
- Enhanced Host Controller Interface. See EHCI
- enumeration
  - defined 89
  - steps 90–95
  - tips 96–97
- EOB 56, 59
- EOP 44, 383, 427, 432
  - low speed 385
  - See also HSEOP
- EPROM (program memory) 140
- ERDY Transaction Packet 59
  - control transfers and 65
  - Latency Tolerance Message and 406
- ERR 49
  - PID 43
- error checking 50–53
- Error condition, Request 122
- eSATA 3
- Ethernet
  - standard 169
  - vs. USB 3, 10
- Ethernet control model 169, 170
- Ethernet emulation model 169, 170
- example code
  - descriptors 281–285
  - detecting devices 252–275
  - HID application 320–343
  - using 143
  - WinUSB application 350–372
- exit latencies 135
- EXT PID 43, 44
- Extensible Host Controller Interface. See xHCI
- extension cable 454–455
- eye pattern template 446
- EZ-USB 148, 152–156
  - development boards 145
  - See also Cypress Semiconductor

## F

- FDO 211
- Feature item (HID) 298, 299
- Feature report 339–343
  - API 318
- filter DO 211

Firewire. See IEEE-1394  
 firmware  
   example code 143  
   for control transfers 123–124  
   interrupts and 45  
   overview 137–138  
   portability 139  
   See also specific chip  
 flash drive. See mass storage  
 floppy drive 185  
 flow control condition 59  
 Frame Number field 433  
 frame, defined 33  
 Framework, Microchip USB 152  
 Freescale Semiconductor 175  
 FT232BM 158  
 FT232BM/2232H/4232H. See USB UART  
 FT245BM 158  
 FT245BM/2232H/4232H. See USB FIFO  
 FTDI  
   chips 158  
   See also specific chip, USB UART, USB  
     FIFO  
 full speed 4  
   cable segment 440  
 function, USB 18  
 FUNCTION\_SUSPEND 127, 128, 405–406

## G

galvanic isolation 465  
 garbage collection 244  
 generic parent driver 214  
 Get Configuration 132  
 Get Descriptor 93, 130  
 Get Idle 289, 290  
 Get Interface 133  
 Get Max Lun 188  
 Get Port Status 92, 122  
 Get Protocol 289, 291  
 Get Report 289, 290  
 Get Status 126  
 Global item (HID) 302–311  
 global suspend 400  
 Globally Unique Identifier. See GUID

GNU GCC compiler 156  
 Gold Tree 419  
 GPIB. See IEEE-488  
 GT/s 437  
 GUID 219–221  
   See also device interface GUID; device set-  
     up GUID

## H

handle 249  
   closing 264  
   obtaining 262–264  
   WinUSB 350–352  
 handshake phase 43  
 handshake, high-speed detection 385, 428–  
   429  
 hardware key 227  
 Hayes command set 169  
 header sequence number 55  
 hibernation 407  
 HID  
   API summary 315–320  
   boot protocol 285  
   descriptors 281–289  
   Feature report 318, 339–343  
   finding a device 320–327  
   Global item 302–311  
   INF file 239  
   Input report 317–318, 330–339  
   Local item 311–314  
   Main item 298–302  
   Output report 317–318, 328–330  
   overview 180–182  
   physical descriptor 314  
   report structure 295–298  
   requests 289–292  
   requirements 278–281  
 HID Descriptor Tool 296  
 HidD\_FreePreparedData 343  
 HidD\_GetAttributes 321–323  
 HidD\_GetFeature 318, 341–343  
 HidD\_GetHidGuid 253  
 HidD\_GetInputReport 318, 343  
 HidD\_GetPreparedData 323–324

## Index

- HidD\_SetFeature 318, 339–341
  - HidD\_SetOutputReport 318, 341
  - HIDmaker 293
  - HidP\_GetButtonCaps 327
  - HidP\_GetCaps 324–326
  - HidP\_GetValueCaps 327
  - high speed 4
    - cable segment 440
    - detecting device removal 448
    - reason for selecting 444
    - switching to 447
  - high-bandwidth endpoint 78, 84
  - high-power device 392
  - High-speed Data J and Data K 428
  - high-speed detection handshake 385, 428–429
  - High-speed Differential 0/Differential 1 428
  - High-speed Disconnect 429
  - High-speed Idle 429
  - High-speed Squelch 429
  - HI-TECH C compiler 152
  - HNP 474–476
  - host
    - computer 15
    - controller 15, 216–217
    - embedded 471–485
    - latency 88
    - responsibilities 20–22
    - See also OTG; driver
  - Host Negotiation Protocol. See HNP
  - host-to-host communications 205–207
  - hot pluggable 2, 454
  - Hot Reset 438
  - HSEOP 429, 432
  - HSSOP 429
  - hub
    - class 388
    - Container ID 115
    - controller (SuperSpeed) 387
    - controller (USB 2.0) 375
    - defined 373
    - driver 215
    - INF file 239
    - maximum in series 455, 461
    - power 396–399
    - root 15, 376
    - USB 2.0 374–385
    - USB 3.0 385–388
  - hub depth 55, 387
  - human interface device class. See HID
  - Hyde, John 483
- I**
- I/O request packet 87, 210
  - I2C
    - compared to USB 3
    - EEPROM 141
    - USB transceiver 484
  - IAD. See interface association descriptor
  - IAR Systems 156
  - ICC 192
  - ICCD 193
  - icon
    - USB 2.0 452
    - USB 3.0 460
  - ID pin 452
  - Idle 427
    - See also High-speed Idle 429
  - idProduct 102
    - See also Product ID
  - idVendor 102
    - See also Vendor ID
  - IEEE 802.3 169
  - IEEE-1284 190, 191
  - IEEE-1394
    - compared to USB 3
    - vs. USB 11
  - IEEE-488 197, 198
    - compared to USB 3



- impedance
    - characteristic (full/high speed cable) 451
    - characteristic (SuperSpeed cable) 458
    - measuring 446
    - output (high speed) 445
    - output (low/full speed) 444
  - Imports statement 244
  - IN
    - defined 34
    - PID 42
    - transaction 35
  - InBand Reset 438
  - INF file 231–240
    - driver key and 231
    - enumeration and 94
  - Inf2Cat 236
  - Infineon 148
  - Infrared. See IrDA
  - Input item (HID) 298–300
  - Input report 330–339
    - API 317–318
  - inrush current 398
  - insertion loss, differential 461
  - instance key 227
  - Intel controllers 148
  - inter-chip connection 455–456
  - interface
    - alternate 108
    - class code 109
    - defined 105
    - descriptor 107–110
    - getting and setting 133
  - interface association descriptor 105–107
    - CDC 171–172
  - interface chip, USB 156–161
    - See also microcontroller
  - Interop 245
  - InteropServices 244
  - inter-packet delay 434
  - interrupt transfer 75–80
    - purpose 38
  - IntPtr 249
  - IOCTL (media serial number) 177
  - IP (Internet Protocol), to access device 455
  - IrDA bridge 183–184, 469
  - IrLAP 183
  - IRP 87, 210, 214–215, 412
  - ISDN 169, 170, 172
  - iSerialNumber 102
    - See also serial number
  - ISO/IEC 26907/8 466
  - isochronous delay 135
  - Isochronous Timestamp Packet 53, 82
  - isochronous transfer 80–85
    - purpose 38
  - isochronous, defined 80
  - isolation, galvanic 465
  - ISP1181B/83 158
  - ISP1301 484
  - ISP1362 484
  - ISP1582/3 157
  - ISP1583 188
  - ISP1761 485
  - IsReference 250
  - ITP. See Isochronous Timestamp Packet
- ## J
- J state 426, 428
  - jitter 433
  - JoyWarrior 182
  - Jungo Ltd. 175, 203
- ## K
- K state 426, 428
  - keep-alive signal 400
  - Keil compiler 153
  - kernel mode 210–211
  - kernel32.dll 245
  - kernel-mode client driver 213–215
  - Keyspan 455
  - KeyWarrior 182
  - KLKUSB220 175
  - KMDF 218
    - library 236
  - K-Micro 175
- ## L
- Last Packet Flag. See LPF

# Index

- latency
    - host, general 88
    - power management 135
  - Latency Tolerance Message 406
    - bit 126
    - Set Feature and 128
  - layered driver model 209–210
  - legacy hardware 8–9
    - See also parallel port, RS-232
  - length, cable
    - USB 2.0 454–455
    - USB 3.0 461
  - LFPS 404, 437
  - link
    - defined (USB 2.0) 399
    - states 403–405
    - training 438
  - Link Control Word 54
  - link layer 437
  - Link Management Packet 53, 59
  - Link Power Management. See LPM
  - link, defined (USB 3.0) 437
  - Linux USB Project 216
  - LMP. See Link Management Packet
  - Local item 311–314
  - lockable storage device 185
  - Logical Minimum and Maximum (HID) 305, 308–310
  - logo
    - Certified USB 415, 419
    - Windows 422–424
  - low speed 4
    - cable segment 440
    - cable specification 450
    - EOP 385
    - keep-alive 400
  - low-frequency periodic signaling 437
  - low-power device 392
  - LPC 292x 148
  - LPC214x 148
  - LPC3180 484
  - LPF 56, 83
  - LPM 399
    - transaction 402
  - LTM\_ENABLE 127, 128
  - Lun 188
- ## M
- Main item (HID report) 298–302
  - managed code 244
  - marshaling 245–247
  - mass storage 184–189
    - INF file 239
    - UASP 27
  - maximum packet size 101, 111–112
  - MCCI 175
  - MCF5482 175
  - MDATA 42, 52–53
  - Media Transfer Protocol 195
  - medical device. See personal healthcare class
  - message pipe 38
  - Micrel Inc. 401
  - Micro-A plug 472
  - Micro-AB receptacle 472
  - Micro-B connector 451, 452
    - cable length and 454
    - See also USB 3.0 Micro-B connector
  - Microchip Technology 148
    - controllers 484
    - USB Framework 293
    - See also specific chip; PICBASIC PRO; C18 C compiler
  - microcontroller
    - USB 147–156
    - See also interface chip, USB
  - microEngineering Labs, Inc. 152
  - microframe, defined 33
  - Microsoft
    - OS descriptor 116
    - Remote NDIS 175
    - RNDIS 169
    - Universal Audio Architecture 169
    - WDF 7
    - WDM 213
    - See also .NET; Windows
  - Microwire
    - compared to USB 3
    - EEPROM 141

MIDI 165, 166, 167  
 compared to USB 3  
 Mini-AB receptacle 472  
 Mini-B connector 451, 452  
 miscellaneous device class 101  
   IAD and 106  
 MMC 185  
 modem  
   ADSL 169, 170  
   command set 169, 174  
   driver 175  
   telephone 172  
 monitor control (HID) 180  
 MouseWarrior 182  
 MSIL 244  
 Multi-interface Function Device Class  
   Codes 106

## N

NAK 47  
 NAK PID 42  
 NDIS 169  
 .NET 212–213  
   API calls and 243–252  
   finding a device 252–262  
   See also example code.  
 NET2272 157–159  
   RDK 145–146  
 network  
   accessing devices over 455  
   See also Ethernet control model; Ethernet  
   emulation model; NDIS  
 noise sources 462  
 notification  
   CDC 170  
   device (Windows) 265–275  
 notification (SuperSpeed) 57  
   Function Wake 406  
   Latency Tolerance Message 406  
 Notification usage 111  
 NRDY  
   control transfers and 65  
   Transaction Packet 54  
 NRZI 430  
 NTamd64 235  
 NT-based 12  
 NTia64 235  
 NTx86 235  
 NumP 57, 58, 59  
   in bulk transfers 72  
   in control transfers 65  
 NXP Semiconductors 148  
   controllers 484  
   See also ST-NXP Wireless; specific chip  
 NYET 48  
   control transfers and 65  
   in bulk transfers 71  
   in control transfers 121  
   PID 42

## O

OBEX 172, 175  
 OHCI 216  
   interrupt transfers and 78  
   vs. UHCI 216–217  
 On-The-Go. See OTG  
 Open Host Controller Interface. See OHCI.  
 Ordered Set 438  
 oscillator, in device 139  
 OTG  
   A-device and B-device 472  
   bus current 478  
   cables 477  
   chips 482–485  
   connector 472  
   descriptor 115, 479  
   requirements 472, 473–479  
   Supplement 472  
   targeted peripheral list 479  
   user messages 479  
 other\_speed\_configuration descriptor 105  
 OUT  
   defined 34  
   PID 42  
   transaction 35  
 Output item (HID) 298, 299  
 Output report 328–330  
   API 317–318

## Index

- over-current protection 397
- Oxford Semiconductor 485
- OXU210HP 485
  
- P**
- packet
  - delay between 434
  - sequence (USB 2.0) 44–45
  - short. See short packet
  - size, maximum 101, 111–112
  - SuperSpeed 53–59
- Packet ID. See PID.
- Packets Pending 56, 58
- padding (HID) 314
- page description language 190, 191
- parallel port
  - adapter 8
  - compared to USB 3
  - converting from 9–10, 204–205
- passphrase, mass storage 185
- PC
  - as device 145–146
  - connecting two 205–207
  - See also host
- PCI device board 145–146
- PCI Express (PCIe) 457
- PCM2702/PCM2900 168
- PDL 190, 191
- PDO 211
- PDT 187
- Periodic usage 111
- peripheral 19
  - See also device
- personal healthcare class 189–190
- phase, transaction 41–44
- Phase-locked SOFs ECN 399
- phone. See telephone; cell phone
- physical descriptor 314
- physical interface device 180
- Physical Minimum and Maximum (HID) 306, 308–310
- PIC. See Microchip Technology; specific chip
- PIC18 controllers 148
  - See also specific chip
- PIC18F4550 148–152
- PIC24FJ 484
- PIC32MX 484
- PICBASIC PRO 152
  - descriptors 281
  - HID code 293
  - WinUSB and 349
- PID (packet ID) 41–44, 433
  - error-checking bits 51
  - sequencing 53
- PID (physical interface device) 180
- PIMA 15740 195–196
- PING (SuperSpeed) 407
- PING (USB 2.0) 49
  - control transfers and 65
  - in bulk transfers 71
  - in control transfers 120
  - PID 43
- PING\_RESPONSE 407
- ping-pong buffer 139
- PInvoke (P/Invoke) 244
- pipe
  - defined 36
  - stream and message 38–39
- PL-2305 192
- PL-2501 206
- Platform Invocation Services 244
- Plug-and-Play 211, 214
- PLX Technology 145–146, 158
- PNF 238, 240
- PnP 211, 214
- point of sale 181
- pointer 249
- port
  - defined 19
  - indicator (hub) 388
- PORT\_RESET 122
- POS 181
- power
  - bus. See bus power
  - switch, soft-start 401
- Powered-B connector 460
- PowerOn Reset 438
- PRE PID 43, 44, 377, 381
- precompiled INF file 238

printer class 190–192  
 INF file 239  
 See also parallel port  
 Product ID  
 in descriptor 102  
 INF file and 236  
 Prolific Technology 188, 192, 206  
 propagation delay 454  
 property page 225, 241  
 protocol analyzer  
 hardware 410–412  
 software 412–413  
 PS/2 182  
 PSTN 170, 172  
 PtrToStringAuto 245  
 Public switched telephone network. See PSTN  
 pull-up resistor 385, 392, 444

## Q

quadruple buffers 139  
 QuickUSB Module 145

## R

RAM  
 data memory 141  
 program memory 140, 141  
 raw input 182  
 ReadFile 317, 330–339  
 real-time transfers. See speed  
 receiver  
 high speed 445  
 low/full speed 442  
 SuperSpeed 457  
 reference variable 249–250  
 RegisterDeviceNotification 265–269  
 registry 226–231  
 Remote NDIS. See RNDIS  
 remote wakeup 402  
 bit 126  
 removable devices and media 188  
 repeater/forwarder (SuperSpeed hub) 386–387  
 report descriptor 286–289

Report ID 303–304  
 request  
 class specific 136  
 standard 124–135  
 vendor specific 136  
 Request Error condition 122  
 Request Type 118  
 reset  
 enumeration and 92, 93  
 hot 438  
 SuperSpeed 438  
 warm 403  
 Reset state 427–428  
 Resume state 401, 427  
 Retry bit 56  
 rise time 454  
 RNDIS 169, 175  
 ROM (program memory) 140  
 Root 2 USB Test Host 414  
 root hub 15, 376  
 Route String 56, 58, 387  
 RPM Systems 414  
 RS-232  
 adapter 8  
 converting from 204  
 See also COM port, virtual; EIA/TIA-232  
 RS-485 3, 455

## S

S1-S4 power states 407–408  
 SafeHandle 249  
 scrambling 436  
 SCSI 185, 187  
 USB Attached. See UASP  
 SDK 212, 245  
 Sealevel Systems 465  
 SECURITY\_ATTRIBUTES 262  
 selective suspend 400  
 Self-Powered bit 126  
 self-powered device 392  
 Sequence Number 55–56  
 sequence number, header 55  
 serial interface engine 138

# Index

- serial number
  - content security and 177
  - driver installation and 242
  - IOCTL for media 177
  - mass storage and 187
  - registry and 227
- serial port. See COM port, virtual; RS-232; RS-485
- Series A. See Standard-A connector
- Series B. See Standard-B connector
- service interval 56, 112
- service key 231
- service, defined 39
- Session Request Protocol 476
- Set Address 93, 129
- Set Configuration 132
- Set Descriptor 131
- Set Feature 128
- Set Idle 289, 292
- Set Interface 133
- Set Isochronous Delay 95, 135
- Set Port Feature 122
- Set Protocol 289, 292
- Set Report 289, 291, 318
- Set SEL 95, 135, 406
- Setup
  - Data Packet 65
  - required ACK 70
  - transaction 35
- SETUP PID 42
- Setup stage 62, 118–119
  - SuperSpeed 65
- SetupAPI log file 240
- setupapi.dll 245
- SetupDiDestroyDeviceInfoList 253, 261
- SetupDiEnumDeviceInterfaces 253, 255–258
- SetupDiGetClassDevs 253, 254–255
- SetupDiGetDeviceInterfaceDetail 253, 258–261
- shielding 464
  - requirement (USB 2.0) 451
- short packet 45
  - WinUSB 360
- SIE 138
- signature, digital 423–424
- signed driver. See digital signature
- SilentInstall 229
- Silicon Laboratories
  - controller chip 145, 148, 161
  - development board 145
- Single-ended 0/1 426
- sleep (Windows) 407
- Sleep state 399, 401–402
- smart card 192–194
  - INF file 239
- SMSC
  - controller chips 148, 188
- SnoopyPro 413
- SOF 43–44, 385
  - and low-power states 399
  - PID 42
  - synchronizing to 82
- soft-start power switch 401
- SOP 427
  - See also HSSP 429
- Sourcequest, Inc. 413
- SourceUSB 413
- SPC 187
- specification
  - Certified Wireless USB 466
  - class 164
  - ECNs 14
  - OTG 472
  - USB 1.0, 1.1 11
  - USB 2.0 12–13
  - USB 3.0 13
  - See also specific class
- speed
  - bus 4
  - considerations 16–18
  - deciding on 142
  - detecting 92–93
  - detecting device 384–385
  - USB 2.0 hub 383–385
  - See also bandwidth; throughput
- SPI
  - compared to USB 3
  - EEPROM 141
- SPLIT PID 43, 44

- split transaction 379–382
  - Squelch 429
    - detecting 446
  - SRP 476
  - SSPLIT 380–381
  - ST-NXP Wireless 158, 188
    - controllers 484
    - transceiver 484
    - See also NXP Semiconductors
  - ST7260 148
  - ST7265X 148
  - ST7268x 148
  - STALL 47–48
    - in control transfer 50, 65, 121, 122, 123
    - PID 42
    - Transaction Packet 54
  - Standard Microsystems Corporation. See SMSC
  - Standard-A connector 452
  - Standard-B connector 451
    - See also USB 3.0 Standard-B connector
  - standby state 407–408
  - star, tiered 15–16
  - Start of Frame. See SOF
  - Start-of-High-speed-Packet 429
  - Status Change endpoint 383, 387, 393
  - status codes 47–49
  - status phase. See handshake phase
  - Status stage 62, 121–122
    - SuperSpeed 65
  - Std A, Std B. See Standard-A connector; Standard-B connector
  - still image
    - INF file 239
  - still image class 194–197
  - STMicroelectronics 148
    - DFU driver 179
  - Stream ID 58
  - stream pipe 38
  - string descriptor 113–114
  - structure, passing 251–252
  - Subtype (Transaction Packet) 54, 57
  - SuperSpeed 4
    - detection circuit 457
    - enumeration 95
    - See also USB 3.0
  - SuperSpeed endpoint companion
    - descriptor 112–113
    - burst transactions and 57
  - SuperSpeed USB device capability
    - descriptor 115
  - Suspend state 400–401
    - high speed 448
    - SuperSpeed 403, 405–406
  - Symbol 437
  - symbolic link 221
  - SYNC field 431, 433
  - Synch Frame 134
  - synchronization type 111
  - system exit latencies 135
  - %SystemRoot% 232
- ## T
- targeted peripheral list 479, 481
  - TDR 446
  - telephone
    - cell 170
    - network. See PSTN
  - termination, high speed 445–447
  - test and measurement class 197–198
  - test modes 127, 128, 435–436
  - testing
    - compliance 415–419
    - equipment 410–414
    - logo 419–424
  - Tetradyne Software, Inc. 203
  - Texas Instruments 148, 168, 188
  - Thesycon Systemsoftware & Consulting GmbH 175, 203
  - threads (host programming) 87
  - throughput 24
    - maximizing 86–88
  - TIA/EIA-485. See RS-485
  - tiebreaker 60
  - tiered star 15–16

# Index

- timeout
    - HidD\_GetFeature 342
    - HidD\_SetFeature 341
    - ReadFile 330–331
    - WinUSB 360
    - WriteFile 317–318
  - timing reference (device) 139
  - TMC. See test-and-measurement class
  - token phase 43
  - topology, bus 15–16
  - TP. See Transaction Packet
  - Trace Systems, Inc. 293
  - traffic generator 414
  - training, link 438
  - transaction
    - burst 57
    - burst (isochronous) 84
    - elements (USB 2.0) 39–46
    - split. See split transaction
    - SuperSpeed 53–59
  - Transaction Packet 53
  - transaction translator 377–382
  - transceiver 138
    - USB 2.0 439–449
    - USB 3.0. See transmitter (USB 3.0); receiver (USB 3.0)
  - transfer
    - defined 39
    - types 37
    - See also bulk transfer; control transfer; interrupt transfer; isochronous transfer
  - transmitter (USB 3.0) 457
  - trusted publisher 423
  - TUSB3200A 168
  - TUSB3210/3410 148
  - TUSB3410 184
  - TUSB6250 148, 188
  - twinaxial cable 457
  - twisted pair 457, 463–464
- ## U
- U0-U3 link states 403–405
  - U1\_ENABLE and U2\_ENABLE 127, 128
  - U3. See Suspend state
  - UAA 169
  - UASP 27, 185
  - UFI 185
  - UHCI 216
    - vs. OHCI 216–217
  - UM232R/UM245R modules 161
  - UMDF 218
  - Universal Audio Architecture 169
  - Universal Host Controller Interface. See UHCI
  - universally unique identifier 115
  - unmanaged code 244–247
  - UnregisterDeviceNotification 275
  - UOWN 149
  - UPS unit 180
  - upstream 15
  - URB 214–215, 412
  - Usage (HID) 287, 311, 312
  - Usage Page 286, 304
  - Usage Tables 181, 296, 305
  - USB
    - benefits for developers 5–7
    - benefits for users 2–5
    - compared with other interfaces 3
    - history 11–15
    - icon 452, 460
    - limits 7–10
    - logo 415, 419
    - speeds 4
    - topology 15–16
      - vs. Ethernet 10
      - vs. IEEE-1394 11
    - See also specification
    - USB 1.0, USB 1.1. See USB 1.x
    - USB 1.x 11
      - hub 383
    - USB 2.0
      - history 12–13
    - USB 2.0 Extension (device capability descriptor) 114
    - USB 2.0 Phase-locked SOFs 399



USB 3.0  
     frequently asked questions 27–30  
     history 13  
     See also SuperSpeed  
 USB 3.0 Micro-B connector 458  
 USB 3.0 Standard-A to USB 3.0 Standard-A  
     cable 461  
 USB 3.0 Standard-B connector 458  
 USB Attached SCSI Protocol 27  
 USB FIFO 159–161  
 USB Implementers Forum. See USB-IF  
 USB Server 455  
 USB UART 159–161  
     for host-to-host communications 207  
 USB2005/USB222x 148  
 usb8023.sys 175  
 USBCAMD 202  
 usbccgp.sys 175, 214  
 USBCV 416  
 USBee EX2 Experimenter's Board 145  
 usbhub.sys 215  
 USBI2C/IO 145  
 USB-IF  
     about 7  
     compliance tests 415–419  
 usbport.sys 215  
 usbscan.sys 196  
 usbser.sys 175  
 usbstor.sys 188  
 USBTMC. See test-and-measurement class  
 usbvideo.sys 202  
 USBwatch 293  
 user mode 210  
 user32.dll 245  
 user-mode client driver 213  
 using statement 244  
 UUID 115  
 UWB 466

## V

V.250 modem standard 169  
 value variable 249–250  
 variable type 249

## VBUS

capacitance 393  
 detecting 393  
     USB 3.0 hub and 385  
     voltage 390  
 Vendor ID  
     in registry 227  
     INF file and 236, 240  
     obtaining 10  
     reading (HID) 321–323  
 Vendor-specific class 101  
 Verilog 138  
 VHDL 138  
 ViCAM-III 202  
 video class 198–202  
 virtual COM port 160, 173–175  
     driver 175  
     See also communications device class; USB  
         UART; USB FIFO  
 Vista Imaging 202  
 Visual Basic. See example code; .NET  
 Visual C#. See example code; .NET  
 Visual C++ 244  
 voltage  
     back 393  
     bus 390  
     output (USB 2.0) 449  
     See also VBUS

## W

W81E381 194  
 Warm Reset 403, 438  
 WDF 7, 217  
 WDK 217–219, 245  
     devcon example 220  
     GUIDs and 219  
 WDM 213, 217  
 WHQL 238  
 WIA 196  
 WiMedia Alliance 466  
 Winbond Electronics Corporation 194  
 wIndex 119  
 %windir% 232  
 WindowProc. See WndProc

## Index

- Windows
    - API 212
    - audio support 169
    - CDC support 175
    - content security support 177
    - Device Manager 223–226
    - HID support 184
    - logo 422–424
    - mass storage support 188
    - power management 407–408
    - printer support 192
    - registry 226–231
    - smart card support 194
    - video support 202
  - Windows 7 13
  - Windows 95 11
  - Windows 98 11
  - Windows driver
    - irda.sys 184
    - usb8023.sys 175
    - usbccgp.sys 175
    - usbhub.sys 215
    - usbport.sys 215
    - usbscan.sys 196
    - usbser.sys 175
    - usbstor.sys 188
    - usbvideo.sys 202
  - Windows Driver Foundation 7, 217
  - Windows Driver Kit. See WDK.
  - Windows Driver Model 213
  - Windows Hardware Quality Labs 238
  - Windows NT 12
  - Winqual 422–423
  - WinUSB
    - assigning 349–350
    - firmware 346–349
    - INF file 235
    - requirements 345–346
    - See also WinUSB\_XXXX functions
  - WinUsb\_ControlTransfer 368–371
  - WinUsb\_Free 371–372
  - WinUsb\_Initialize 350–352
  - WinUsb\_QueryInterfaceSettings 352–354
  - WinUsb\_QueryPipe 354–358
  - WinUsb\_ReadPipe 366–367
  - WinUsb\_SetPipePolicy 359–364
  - WinUsb\_WritePipe 364–366
  - wire gauge. See AWG
  - Wireless Controller class 101
  - wireless interface 465–469
  - wireless mobile communications 169, 170
  - Wireless USB 466
    - device capability descriptor 114
  - WirelessUSB (Cypress) 466–468
  - wLANGID 114
  - wLength 119
  - WM\_DEVICECHANGE 265, 266
  - wMaxPacketSize 111
  - WMC 169, 170, 172
    - driver 175
  - WndProc 265, 269–270
  - WPF subsystem 192
  - WriteFile 317, 328–330
  - wValue 119
- ## X
- xHCI 216
- ## Z
- zero-length Data Payload 54
    - in control transfer 68
  - zero-length packet. See ZLP
  - ZigBee 469
  - ZLP
    - defined 45
    - in control transfer 50, 68, 120, 121