

Index

- Aerodynamics
 - aircraft, 24, 35
 - compressor, 254
 - turbine, 269
- Acceleration
 - and climb, 62
 - horizontal, 27, 62
 - takeoff, 63
- Additive drag, 193
- Adiabatic flame temperature, 332
- AEDsys software, 11
 - AEDsys program, 12
 - constraint calculations, 39, 195
 - contour plots, 48, 74, 92, 195
 - mission calculations, 72, 195
 - performance calculations, 41, 121, 156, 158, 170, 173, 190, 206, 234, 356, 483, 497
 - AFTRBRN program, 13, 384
 - ATMOS program, 12, 515, 516
 - COMPR program, 12, 254, 264, 269, 292, 295
 - EQL program, 13, 332, 335, 339, 368, 384
 - GASTAB program, 12, 443, 454
 - INLET program, 13, 443, 457, 484
 - KINETX program, 13, 339, 355, 368, 372, 384, 392, 402, 411
 - MAINBRN program, 13, 368
 - NOZZLE program, 13, 479, 481, 498
 - ONX program, 12, 96, 115, 126, 173
 - TURBN program, 12, 254, 292, 295
- Afterbody drag, 199
- Afterburner, 328
 - design tools, 384
 - efficiency, 108
 - fuel-air ratio, 105, 111
 - piloted, 390
 - screech and howl, 385
 - total property ratios, 103
 - vee-gutter, 328, 391, 415
- AFTRBRN program, 13, 384
- Air partitioning, 369
- Air-to-Air Fighter (AAF)
 - afterburner design, 404
 - constraint analysis, 39, 185, 222
 - component
 - operating lines, 249
 - performance, 242, 249
 - engine cycle analysis
 - parametric, 126
 - performance, 172
 - engine
 - design parameters, 178, 220
 - performance, 224
 - epilogue, 507
 - exhaust nozzle design, 492
 - fan design, 300
 - global and interface quantities, 241
 - high-pressure compressor design, 313
 - high-pressure turbine design, 307
 - inlet design, 483
 - installed performance, 504
 - low-pressure turbine design, 317
 - main burner design, 394
 - operational envelope, 184
 - Request for Proposal (RFP), 13
 - sizing the engine, 207
 - theta break, 245, 299
 - throttle ratio (TR), 47
 - thrust loading, 47, 185
 - uninstalled static performance, 227
 - weight, 80
 - wing loading, 47
- Aircraft drag, 24
- Aircraft performance, 19
- Aircraft range, 59
- Airfoils, 254, 262
- Aluminum 2124 alloy, 624
- Annulus, 237, 263
- AN², 292
- ATMOS program, 12, 515, 516
- Atmosphere
 - cold, hot, and tropic day, 8, 511
 - standard, 8, 511
- Augmentor (*see* afterburner)
- Axial interference factor, 538
- Best cruise altitude (BCA), 64
- Best cruise Mach number (BCM), 64
- Blade, cooling of, 281
- Blades, 254, 269
- Bleed air
 - boundary layer, 382
 - engine, 98, 104, 109, 240
- Blowout, 342, 391

- Boundary layer
 - control, 449
 - separation, in diffuser, 360, 431
 - shock separation of, 449
- Bragg criterion, 341
- Braking roll, 31
- Burner, main
 - air partitioning, 369
 - combustor loading parameter (CLP), 345
 - components, 326
 - design parameters, 369
 - design tools, 368
 - efficiency, 108
 - exit temperature profile, 328
 - flow path, 326
 - fuel-air ratio, 105, 111
 - liner cooling, 372
 - map, 165
 - total pressure loss, 380
 - total property ratios, 103
 - types, 577
- Bypass air of supersonic inlet, 369, 378
- Bypass ratio, 104
 - mixer, 105
 - optimum, 491
- Carter's rule
 - compressor, 262
 - turbine, 280
- Cascade, 254
- Carrier
 - approach (wave-off), 35
 - landing, 34
 - takeoff, 34
- Ceiling, service, 33
- Centrifugal stress, 284, 290
- Chemical equilibrium, 332
 - kinetics, 355
 - reactor theory, 339
- Climb
 - and acceleration, 62
 - constant speed, 26, 61
- Combustion
 - Bragg criterion, 341
 - blowout, 342, 391
 - efficiency, 108
 - ignition, 368
 - process, 330
 - reaction rate, 337
 - residence (stay) time, 341, 391
 - stability of, 339, 346
 - systems, 325
- Combustor (*see* Burner, main)
- Combustor loading parameter (CLP), 345
- Component
 - behavior, off-design, 163
 - design performance parameters, 107
 - flow path force on, 237
 - matching, 168
 - operating line (*see* Engine operating line)
 - performance analysis, off-design, 148
- COMPR program, 12, 254, 264, 269, 292, 295
- Compressible flow functions, 8, 547
- Compression, inlet, 419
- Compressor
 - aerodynamics, 254
 - airfoil geometry, 262
 - design parameters, 269
 - efficiency, 106
 - flow path dimensions, 263
 - performance map, 164
 - radial variation, 265
 - repeating stage/row, 255
 - stage design, 254
 - stall or surge, 164
- Constraint analysis, 19
- Control system (*see* Engine control system)
- Convergent nozzle, 465, 478
- Convergent-divergent nozzle, 465
- Coolant mixer, 98, 111, 143
- Cooling air, 98, 104, 240, 281, 372
- Corrected
 - engine speed, 163
 - mass flow rate, 163, 236
 - pressure, 163
 - temperature, 163
- Creep, 287, 625, 639
 - Larson-Miller parameter, 289
- Cruise
 - best Mach number and altitude, 64
 - constant altitude/speed, 25, 63
- Cycle analysis (*see* Engine cycle analysis)
- Degree of reaction, 257, 271
- Design process, 3, 6
- Diffuser (*also see* inlet)
 - afterburner, 328, 365, 387
 - main burner, 326, 362, 375
 - pressure recovery, 359, 362
 - subsonic, 429
 - supersonic, 435, 460
 - total pressure ratio, 102, 109
 - total pressure recovery, 109
 - total property ratios, 102
- Diffuser duct, 326, 328, 358, 429, 435, 460
- Diffuser, dump, 362
- Diffusion factor, 255
- Dilution zone, 327, 369
- Dimensionless engine performance
 - parameters, 163
- Disk
 - of uniform stress, 294
 - shape factor, 295
 - thermal differential stress, 286, 298
 - torsional stress, 297

- Dome, combustor, 327
- Domestic object damage (DOD), 286
- Drag
 - additive, 193
 - afterbody, base, or boattail, 199
 - aircraft, 24, 35
 - exhaust nozzle, 199
 - forebody, 190, 361
 - inlet, 190, 427, 429
 - nacelle, 429
- Dynamic pressure, 10
- Efficiency
 - afterburner, 108, 330
 - burner, 108, 313
 - compressor, 106, 258
 - diffuser, 359
 - fan, 106
 - inlet, 420
 - mechanical power transmission, 109
 - nozzle, 462
 - power takeoff, 109
 - propeller, 591, 602, 621
 - propulsive, 115, 538
 - overall, 115, 538
 - thermal, 115, 538
 - turbine, 106, 279
- Endurance (*see* Loiter)
- Endurance factor (EF), 66
- Energy height, 22
 - constant, maneuver of, 68
- Engine
 - back pressure control, 398
 - control system, 125, 159, 233, 525, 663
 - components, 673
 - logic and processing, 666
 - requirements, 663
 - schedules, 669
 - cooling and bleed air, 98, 240
 - data, 519
 - design, 6, 7
 - fuel system, 239
 - global and interface quantities, 233
 - installed thrust, 23, 38, 55, 189
 - lubrication system, 239
 - operating line, 164, 249, 467, 527, 664
 - performance, 523
 - measures, 539
 - pressure ratio (EPR), 665
 - speed, 157
 - starting, 240
 - shafts and bearings, 239
 - static structure, 238
 - systems design, 238
 - uninstalled thrust, 97, 189
- Engine cycle analysis, Parametric (on-design), 95
 - high bypass ratio turbofan, 571
 - mixed-stream turbofan, 96
 - assumptions, 109
 - component efficiencies, 106
 - computational inputs and outputs, 115
 - engine performance analysis, 110
 - mass flow rates, 104
 - performance, 117
 - station numbering, 96
 - summary of equations, 557
 - total property ratios, 102
 - turbine cooling model, 105
 - turboprop, 590
- Engine cycle analysis, Performance (off-design), 139
 - high bypass ratio turbofan, 577
 - mixed-stream turbofan, 140
 - assumptions, 141
 - component behavior, 121, 163
 - component performance analysis, 148
 - computational inputs and outputs, 152
 - dependent variables, 158
 - high-pressure turbine and coolant mixers—performance, 143
 - independent variables, 141
 - iteration solution scheme, 156
 - summary of equations, 563
 - variation in engine speed, 157
 - turboprop, 597
 - turbojet, 529
- Engine life, 283
- Engine life management, 635
 - development and qualification testing, 655
 - failure modes, 641
 - fracture critical parts, 638
 - inspection, 645
 - laser shock peening (LSP), 639
 - lessons learned, 635
 - lifing concepts, 641
 - nondestructive evaluation (NDE), 638
 - retirement-for-cause, 644
- Enthalpy
 - of formation, 332
 - of reaction, 333
- Equilibrium, chemical, 332
- EQL program, 13, 332, 335, 368, 384
- Equivalence ratio, 331
- Euler pump and turbine equation, 258, 270
- FAIR, 100
- Fan
 - aerodynamics, 254
 - efficiency, 106
 - performance map, 164
 - total property ratios, 102
- Fatigue, 285, 623
- Flame spread, 393
- Flame stability, 324, 346, 389
- Flameholder, 328, 366, 390

- Flameholding, 339
- Flow path force, 10, 237
- Flutter, 285
- Foreign object damage (FOD), 286, 636
- Free-vortex flow (*see* swirl distribution)
- Fuel nozzles, 379
- Fuels, 367
- Fuel-to-air mass flow ratio
 - afterburner, 105, 111
 - main burner, 105, 111
 - overall, 105
 - stoichiometric, 330
- Gas model
 - calorically perfect gas (CPG), 99
 - constant specific heat (CSH), 99, 116
 - modified specific heat (MSH), 116
 - variable specific heat (VSH), 99, 116
 - compressible flow functions, 547
- Gas properties, variation of, 11
- GASTAB program, 12, 443, 454
- Ground roll
 - landing, 31
 - takeoff, 28, 29
- Hastelloy X, 373, 628
- Heat of reaction, 332
- Heating value, 334
- High cycle fatigue (HCF), 285, 639
- Hot day flat rating, 532
- Ignition, 368, 390
- Impulse function, 10, 114, 237, 441, 460
- Inconel 601, 628
- Inlet
 - area, estimate of, 203, 422, 454
 - auxiliary area, 206
 - boundary layer control, 449
 - buzz, 448
 - bypass air, 435, 439
 - drag, 190, 192, 195
 - efficiency, 420
 - external compression, 195, 435
 - flow distortion, 425, 458
 - flow separation from lip, 431, 461
 - functions, 191, 422, 432
 - installation loss, 190, 192, 195
 - internal compression, 195, 433
 - location, 429, 458
 - mass flow characteristics, 443
 - mixed compression, 195, 439
 - off-design behavior of, 422, 433, 453
 - pressure recovery, 109, 142, 422, 440
 - subsonic, 192, 421
 - supersonic, 195, 431
 - critical operation, 446
 - start, 434
 - subcritical operation, 436
 - supercritical operation, 436
 - throat area variation, 434
 - unstart, 434
 - total pressure ratio, 102, 109, 142, 422, 440
 - zero flight speed, 431
- INLET program, 13, 443, 457, 484
- Installed thrust, 23, 38, 55, 189, 191, 206, 543
- Installed thrust specific fuel consumption, 55, 60, 71, 206
- Integral mean slope, 199
- Intermediate zone (*see* Secondary zone)
- Jets
 - round, 347
 - swirling, 352
- KINETX program, 13, 339, 355, 368, 372, 384, 392, 402, 411
- Landing
 - braking roll, 31
 - carrier, 34
 - terminology, 32
 - total distance, 32
- Lapse, thrust, 23, 38
- Larson-Miller parameter, 289
- Level of technology, 107
- Lifing (*see* Engine life management)
- Lift, 24, 35
- Lift-drag polar, 25
- Liner, combustor, 326
- Loading, air, 345
- Low cycle fatigue (LCF), 286, 636, 639
- Lower heating value, 334
- Loiter, 66 *
- Mach number, best cruise, 64
- MAINBRN program, 13, 368
- Mar-M 509, 630
- Mass flow
 - parameter, 9, 142, 237, 547
 - rate, corrected, 163, 236
 - rates, 104
 - ratios, 104
- Master equation, 24
- Material properties, 287, 623
- Micromixing, 340
- Minimum climb time, trajectory for, 48, 74
- Minimum fuel climb, trajectory for, 59, 92
- Mission analysis, 55
- Mission terminology, 17
- Mixer
 - afterburner, 386
 - bypass ratio, 105
 - constant area, 113, 551
 - exit Mach number, constant area, 553
 - influence of, 125
 - off-design performance, 178

- total enthalpy ratio, 113
- total pressure ratio, 114
- total property ratios, 103
- Mixer, coolant
 - total enthalpy ratio, 111
 - total pressure ratio, 103
 - total property ratios, 103
- Mixing
 - fuel-air, 379
 - micro- and macro-, 339
 - jet, 347
 - shear layer, 355, 391
- Nacelle and interference drag, 429
- Nimonic, 634
- NO_x , 331, 370
- Nozzle, exhaust
 - area, estimate of, 205
 - area ratio, 467, 495
 - coefficients, 472, 478
 - convergent, 464, 478
 - convergent-divergent, 465
 - drag, 199
 - efficiency, 462
 - engine operating line, and, 467
 - functions, 191, 461, 467
 - gross thrust, 472, 476
 - coefficient, 472
 - installation loss, 190, 199
 - pressure ratio, 467, 483
 - thrust reversing, 468
 - total property ratios, 103, 471
 - types, 464
- NOZZLE program, 13, 479, 481, 498
- Off-design (*see* Performance analysis)
- On-design (*see* Parametric analysis)
- ONX program, 12, 96, 115, 126, 173
- Optimum bypass ratio, turbofan engine, 577
- Optimum turbine ratio, turboprop engine, 597
- Parametric analysis, 95
- Pattern factor, 384
- Performance analysis, 139
- Plug flow reactor (PFR), 338
- Pollutants, 338, 371
- Polytropic efficiency, 106, 110
- Power, specific, 593
- Power specific fuel consumption, 593
- Power takeoff, 97, 109
- Pressure recovery (*see* Inlet, pressure recovery)
- Primary zone, 326
- Programs (*see* AEDsys software)
- Propeller, 609
 - actuator disk theory, 609
 - advance ratio, 618
 - blade element efficiency, 615
 - blade element theory, 613
 - diameter, 617
 - efficiency, 591, 602, 621
 - efficiency model, 621
 - map, 617
 - speed, 616, 620
 - structural design, 619
 - velocity diagram, 614
- P_s , 22, 48
- Radial variation (*see* swirl distribution)
- Range factor (RF), 65
- Ratio of specific heats, 11
- Ratios, total property, 100
- Reaction, degree of, 257, 271
- Recirculation, 326, 328
- Referencing, 142
- Rene' 80, 633
- Request for Proposal (RFP), 4, 636
 - Air-to-Air Fighter (AAF), 13
 - Global Range Airlifter (GRA), 679
- Residence time, 341, 391
- Reverse thrust, 32, 468
- Rim web thickness, 268
- Rotation, takeoff, 28, 67
- Rotational interference factor, 614
- Secondary zone, 326
- Sensitivity analysis, 135
- Service ceiling, 33
- Shock
 - detached, 367
 - normal, 195, 374
 - oblique, 195, 197, 437, 442
- Software (*see* AEDsys software)
- Solidity, 255, 262, 272, 280
- Solution space, 19
- Space heat release rate, 325
- Specific excess power, weight, 22, 48
- Specific fuel consumption
 - power, 593
 - thrust, installed, 55, 60, 71
 - thrust, uninstalled, 97, 120
- Specific heat (*see* Gas model)
 - ratio, 11
- Specific power, 593
- Specific thrust, uninstalled, 96, 120
- Spool design speeds, 311
- Stage, turbomachinery, 254, 269
- Stage pressure ratio
 - compressor, 258
 - turbine, 279
- Stage parameters of turbine, 273
- Stagnation properties, 9
- Stall, aircraft, 29
- Station numbering
 - high bypass ratio turbofan, 569
 - mixed-stream turbofan engine, 97
 - turboprop, 589

- Stay time (*see* residence time)
- Stealth, 191, 385, 394, 422, 431, 470
- Stoichiometric fuel-air ratio, 330
- Stoichiometry, 330
- Strength, specific, 289
- Stress
- centrifugal, 290
 - rim web, 292
 - rotor airfoil, 290
 - thermal differential, 286, 298
 - torsional, 297
 - uniform, disk of, 294
- Summerfield criterion, 478
- Swirl distribution, 265
- comparison, 268
 - exponential, 267
 - first power, 267
 - free vortex, 266
 - non-free or controlled vortex, 281
- Swirling annular jets, 352, 381
- Takeoff
- acceleration, 63
 - carrier, 34
 - climb angle, 30, 33
 - ground roll, 28, 29
 - rotation, 30, 68
 - terminology, 30
 - total distance, 30
 - weight, 55, 68
- Theta break, 117, 126, 245, 525
- Throttle ratio, 38, 527
- Thrust
- installed, 23, 38, 55, 189, 191, 206, 543
 - internal, 468
 - lapse, 23, 38
 - loading, 19, 21
 - instantaneous, 57
 - specific, 97
 - uninstalled, 97, 190, 192, 541
- Thrust augmentation (*see* afterburner)
- Thrust reversers, 468
- Thrust scale factor, 158, 207, 211
- Thrust specific fuel consumption
- installed, 55, 60, 71
 - uninstalled, 97, 572, 593
- Thrust vectoring, 469
- Titanium 6246 alloy, 627
- Total property ratios, 8, 100, 234
- Turbine
- aerodynamics, 269
 - cooling, 281
 - design, 269
 - design parameters, 283
 - efficiency, 106, 279
 - high-pressure
 - enthalpy ratio, 103, 106
 - off-design performance, 144, 147
 - pressure ratio, 103, 106, 108
 - temperature ratio, 108
 - impulse, 168
 - low-pressure
 - enthalpy ratio, 103, 106
 - off-design performance, 145, 148, 178
 - pressure ratio, 103, 107, 108
 - temperature ratio, 108
 - optimum turbine ratio, turboprop, 597
 - performance, 143, 163
 - reaction, 271
 - stage, 270
 - stage loading parameter, 283
- TURBN program, 12, 254, 278, 292, 295
- Turbofan
- high bypass ratio, 569
 - parametric (on-design) analysis, 571
 - equation development, 571
 - example results, 576
 - exit pressure, 572
 - optimum bypass ratio, 577
 - summary of equations, 572
 - performance (off-design) analysis, 577
 - assumptions, 577
 - equation development, 579
 - example results, 584
 - exit pressure, 579
 - summary of equations, 580
 - mixed-stream
 - parametric (on-design) analysis, 97
 - assumptions, 109
 - equation development, 110
 - example results, 117
 - summary of equations, 557
 - performance (off-design) analysis, 140
 - assumptions, 141
 - equation development, 142
 - example results, 121, 224
 - summary of equations, 563
 - variation in engine speed, 157
- Turbojet (*see* Turbofan, mixed-stream)
- Turbomachinery, 237
- rotor nomenclature, 266
- Turboprop, 589
- parametric (on-design), 589
 - assumptions, 589
 - equation development, 590
 - example results, 597
 - optimum turbine ratio, 597
 - summary of equations, 594
 - performance (off-design), 597
 - assumptions, 597
 - equation development, 597
 - example results, 606
 - summary of equations, 602
 - work interaction coefficient, 590
- Turn, constant velocity/speed, 25, 63

- Units
 - conversion factors, 509
 - system of, 8, 509
- Velocity diagrams
 - of axial flow compressors, 239
 - of axial flow turbines, 253
 - of propellers, 614
- Vortex generators, 431
- Warm-up, 67
- Weight, aircraft, 55
- Weight fraction
 - empty to takeoff, 56, 71
 - instantaneous, 23, 39
 - mission leg, 57
 - summary of equations, 60
 - type A, 57
 - type B, 59
- Weight specific excess power,
 - 22, 48
- Well-stirred reactor (WSR), 338
- Wheel speed, 295
- Wing loading, 19, 21
- Work interaction coefficient, 590
- Zero flight speed, inlet at, 431
- Zweifel coefficient, 278