

INDEX

Use this index in conjunction with the Table of Contents. Acronyms are defined in italics. Listings are under the noun except where an expression is commonly used, in which case the listing is under the adjective (e.g., *Kalman filter* or *multisensor navigation*). When *navigation* is the noun, the listing is under the adjective or the navaid. Some expressions are listed only under the acronym (e.g., FIR, FANS, AGC). Page numbers lead the reader to the vicinity of the topic in the book but not necessarily to all pages on which the expression occurs.

- A-6, 530, 538
- A-200, 605
- AAMP microprocessor, 247
- Aberration, image, 566, 587
- Aborted landing, *see* Bolter; Missed approach
- Aborted takeoff, 7
- Absolute position:
 - defined, 1, 114, 283
- Absorption, *see* Atmosphere
- Absorption ratio, 101
- A/C aircraft
- Acceleration:
 - deck heave, 631
 - effect on gyro drift rate, 345
 - effect on oscillators, 233
 - GPS limit, 248
 - inertial equations, 365 ff
 - VG correction, 434–436*See also* Accelerometer; Vibration
- Accelerometer:
 - bias estimation, 87
 - cross-coupling, 320, 323
 - description, 317–324
 - electrolytic level, 429
 - error model, 323–324
 - flexure pivot, 317, 319–321
 - flight control, 324
 - floated, 320
 - hysteresis, 321
 - gravity level, 428–429
 - micromachined, 321–322
 - multiaxis, 323
 - pendulum, 319
 - PIGA, 323
 - pulse-rebalance, 326
 - rectification in, 323
 - testing, 324
 - thermal effects, 323
 - vibrating beam, 322
 - vibration effects, 320
- Accident rate, autoland, 597–598
- Accuracy, *see* Error
- ACID, *aircraft identification code*, 665, 675
- ACLS, *automatic carrier landing system*, 633
- Acoustic:
 - air data, 417
 - gyroscope, 348
 - target detector, 6
- Acquisition:
 - GPS code, 216
 - Loran, 151
 - radar target, 505
 - star, 574
- A/D, *analog-digital*
- Ada, 51, 539
- Adaptive control, *see* Filter
- ADC, *see* Analog-digital converter
- ADC, *air-data computer*, 409–411
- Adcock loop, 119
- ADDSI, *Army data distribution system interface*, 311
- ADF, *airborne direction finder*, 117
- ADIZ, *Air Defense Identification Zone*
- ADS, *see* Automatic dependent surveillance
- Advisory Circulars, *see* FAA,
- AE, *antenna electronics*, 245
- AEEC, *Airline Electronic Engineering Committee*
- AERA, *automated en-route ATC*, 679
- Aeronautical Radio, Inc., *see* ARINC
- Aeronautical Telecommunications Network, 671
- Aerosols, 419
- AFCS, *automatic flight control system*
- Africa, 167
- AFSCF, *Air Force Satellite Control Facility, US*, 208
- AGC, *automatic gain control*, 233, 247, 507
- AGL, *above ground level*
- AGR, *air-to-ground ranging*, 504
- AH, alert height, 599
- AH-1 helicopter, 417
- AH-64D helicopter, 415
- AHRS, *attitude and heading reference system*:
 - complex dg/vg, 426, 430, 433–436
 - with Doppler radar, 450
 - with GPS, 347
 - gyroscopes for, 325

- AHRS, *attitude and heading reference system*
(*cont'd*)
with magnetic compass, 443
with navcom, 14
simple inertial, 389
- AIM, *Airman's Information Manual*, 645
- Air, properties, *see* Atmosphere; Ionosphere;
Troposphere; Weather
- Airbus HUD, 637
- Air carrier, 3, 96, 656, 676
- Air Carrier Operating Certificate, 644
- Aircraft, types, 3–7, 659
- Aircraft carrier:
alignment, INS, 377
deck dimensions, 630–631
deck motion, 631
operations, 631–632
optical landing aid, 633–634
landing systems, 630 ff
Tacan, 633, 636
- Air data:
boom, 395
computer, 409–411
distributed ports, 421
helicopter, 413 ff
history, 400
hypersonic, 421
optical, 418 ff
smart probes, 424
system, 393 ff
- Air Force, *see* United States
- Airport:
capacity, 681
control tower, 655
cornerpost fix, 659
ILS installation, 608, 618
lighting, 600–601, 651
reliever, 681
sensitive area, 620
surface detection radar, 604
surface navigation, 9, 605, 638
surface reflection, 619
surveillance radar, 664–667, 683
traffic control, 642 ff
See also Approach; Departure; Ground control;
Runway
- Airspace:
capacity, 681
Class A and B, 645
controlled, 644–645
oceanic control area, 680–681
organization of, 645–646
positive control, 645
special use, 646
terminal control, 645, 655
uncontrolled, 645–646
US airway system, 646–649
See also Air traffic management
- Airspeed:
calibrated, 397, 406–407
damping of INS, 67–68
during carrier landing, 631
equivalent, 397
“hold,” 15
indicated, 397
Mach calculation, 405
true, 407, 418
- Air traffic management, 642 ff
advisory, 658, 670, 686
alert, 686
blocks, 12
China, 13
display, 673–675
oceanic, 12, 13, 660–661
positive control, 12, 645
procedural, 13
radar, 12, 664–667
railroad precedent, 13
Russia, 12–13
undeveloped areas, 13
vs. on-board, 675–676
See also Airport; Airspace; Capacity; Landing;
Mode-C; Separation
- Airway:
area navigation, 42–43
dimensions, 646–649
jet route, 646
low altitude, 646
steering, 41–42
US structure, 646–649
Victor, 646
- AJ, *anti-jam*, 230. *See also* Jamming
- ALA-52, 497
- Alarm:
limit, 266
navaid integrity, 11
radar, false, 540
star selection, 583
- Alaska, 152
- Aliasing, 247
- Alert:
conflict, 678
flag, GPS, 221
height, 599
limit, GNSS, 263, 266
TCAS, 684
- Alford loop, 123–124
- Alignment, 317 ff
avionics, 703
azimuth, 86
directional gyro, 446
coarse, 382
fine, 383
gyrocompassing, 384 ff
maneuver-match, 388
memory, 381
numerical example, 392
optical, 381
preflight, 592
runway, 381
stellar-inertial, 560, 592–593
transfer, 380–388, 446
vertical gyro, 446
See also Calibration
- Allan variance, 190–192, 208
- Allied Signal, 497
- Almanac:
GLONASS, 251
GPS, 220, 224–225
star, 556
- Alpheratz, 571, 573
- Altimeter:
baro-inertial, 297, 375
barometric, 11, 644

- for approach, 600
- for traffic control, 644
- in celestial navigator, 575
- GPS-inertial, 86
- inertial, 374
- Mode-C, 665–667
- pressure, 394, 396
- radar, 494–498
- radar landing, 599, 606
- setting, 405, 644
- terrain-matching, 37, 491
- Altitude:
 - astronomical, 556
 - ATM display, 658
 - baro-inertial, 375
 - density, 404
 - indicated, 644
 - inertial, 374
 - hole, radar, 481
 - pressure, 394, 644
 - star (angular), 556
 - See also* Minimum altitude
- Altitude rate, air data, 407
- Ambiguity, navaid, 11, 115
- Amplifier:
 - low noise, 232, 493
 - TWT, 546
- AN/x, U.S. military designation, *see x*
- Analog-digital converters:
 - accelerometer, 320
 - air data, 402
 - frequency-to-digital, 486–487
 - GPS, 246–247
 - radar, 507, 516, 548
- Anchorage, 681
- Anemometer:
 - early flight, 19
 - rotating, 414
- Aneroid, *see* Altimeter; Barometric
- Angle of attack:
 - defined, 30, 399 ff
 - landing, 603
 - probe, 395
- Angle of sideslip, 399 ff
- Aniso-inertia, 343
- Anomaly:
 - magnetic, 437
 - orbital, 187
- Antarctic, 503
- Antenna:
 - Adcock, 119
 - aperture, 101
 - array, GPS, 204
 - ATM radar, 665
 - beam shaping, 483, 513
 - body-fixed, 456–457, 474
 - boresight, 515–516
 - controlled reception pattern, 230
 - dipole, 99 ff
 - directivity, 101
 - DME airborne, 131
 - drift-stabilized, 459
 - electronic scan, 528, 546–547
 - elevation pattern, 507
 - end-fire glide slope, 617
 - farm, 4
 - fixed radiation pattern, 215
 - focused, 516–517
 - glide slope, 616–617
 - GPS airborne, 238, 245
 - GPS ground, 208
 - GPS requirements, 230
 - GPS satellite, 204
 - isotropic radiator, 101
 - Janus, 454
 - leakage, 465, 493
 - localizer, 613–614
 - location for GPS pseudolite, 278
 - log periodic, 613
 - loop, 117–119
 - Loran transmitter, 147
 - marker beacon, 121
 - mechanically scanned, 622
 - MLS airborne, 626
 - MLS ground, 622–623
 - monopulse, 483, 511, 525, 538
 - near field, 463
 - nulls, 110
 - Omega airborne, 169
 - Omega ground station, 156
 - phase center, 511
 - principles, 99–103
 - pseudolite, 278
 - radar altimeter, 492
 - radiated power, 102
 - SAR pattern, 513
 - SAR radar, 512
 - scanned array 546–547
 - sense, 118–119
 - slotted array, 480
 - SPN-46, 635
 - Tacan, 134
 - transponder, 665
 - wave-guide glide slope, 616
 - See also* Aperture; Beam configuration; Centroid; Polarization
 - See also each navaid*
- Antenna placement:
 - aircraft, 4
 - aircraft carrier, 632
- Antenna, stabilized:
 - horizontally, 134, 459, 474, 636
 - track-stabilized, 457, 459
- Anti-jam, 230, *See also* Jamming
- Anti-spoofing, 198, 304
- AOC, *auxiliary output chip*, 248
- AOR, *Atlantic Ocean Region*, 270
- APD, *automated problem detection*, 679
- Aperture:
 - antenna, 101
 - effective area, 101
 - SAR, 517
 - telescope, 565
- APN-81, 490
- APN-154, 634
- APN-194, 493
- APN-202, 634
- Apogee, satellite, 186
- Apollo, 450
- Approach:
 - alarm, 11
 - back course, 613
 - controller, 655
 - converging, 683–684

- Approach (*cont'd*)
 coupled, 609
 crab angle, 603
 description, 8
 fix, 8
 front course, 613
 GPS, 202, 251, 628–630
 ground-controlled, 613, 636
 initial, 652–653
 instrument, 652
 landing, 600–601
 missed, 9, 599
 nav aids allowed, 652
 non-precision, 8, 600, 662
 parallel, 682–683
 radar, 662
 routes, 659
 segments, 652–654
 sink rate, 600
 terminal area, 6
 terminal VOR, 646
 visual, 651
See also Approach; Precision; Landing; Missed approach; PAR
- Approach, precision, 600–607
 GPS, 235
 procedures, 654, 659–660, 662
See also Category of landing; ILS; PAR
- APQ, *available position quality*, 299
- APR, *automated problem resolution*, 679
- Apsides of orbit, 186
- Architecture, system:
 air data, 412
 avionics, 17–18
 central, 18, 94, 283, 489
 decentralized, 93–94, 283
 distributed, 412
 federated, 93–94
- Arctic navigation, 13, 503
- Area navigation, *see* RNAV
- Argentina, 152
- Aries, 553, 576
- ARINC, *Aeronautical Radio Inc.*:
 air data, 725
 characteristics, 19
 DME, 628
 Doppler radar, 730
 GPS receiver, 235, 711, 736
 ILS receiver, 608, 619, 736
 inertial navigator, 364, 724
 marker beacon, 619
 MLS, 621, 736
 multimode receiver, 638
 navigation, 705, 707
 software, 51
See also each nav aid
- ARINC-429 data bus, 693
 air data, 409
 GPS, 234
- ARINC-600, 702
- ARINC-629 data bus, 694
 air data, 409, 413
- Army, *see* United States
- Arrival, *see* Approach
- ARSR, *air route surveillance radar*, 677
- ARTCC, *air route traffic control center*, 677–678, 681
- Artificial horizon, 11
- A-S, *anti-spoofing*, 198, 235, 248
- Ascension Island, 208
- ASDE, *airport surface detection radar*, 604
- ASF, *additional secondary phase factor*, Loran, 143
- ASN-157, 490
- ASR, *airport surveillance radar*, 679
- Astrocompass, 446
- Astrodome, 3
- ATC, *air-traffic control*, 642 ff
- ATCSCC, *air traffic control system command center*, 677
- ATCT, *airport traffic control tower*, 677, 679
- ATE, *automatic test equipment*, *see* Testing
- ATIS, *automatic terminal information service*, 657, 660, 670, 680
- Atlantic Ocean, 13, 152, 270, 651, 680
- ATM, *air-traffic management*, 642
- Atmosphere:
 absorption, 109
 attenuation in fog, 109
 attenuation in rain, 109
 background light, 568–572
 density, 397, 404
 ground wave, 104–106
 radio noise, 105
 refraction, L-band, 298
 refraction, optical, 35, 578
 sky wave, 106–108
 specific heat ratio, 397
 standard, aerodynamic, 397, 644
 standard, refraction, 196
 turbulence, 513, 578
See also Ionosphere; Troposphere
- ATN, *Aeronautical Telecommunications Network*
 671
- ATR, *Austin-Trumbull radio rack*
- Attitude:
 “hold,” 15
 inertial, 315–316
 integration, 349
 vertical gyro, 431–434
- Augmentation, GPS, 268 ff
- Australia, 158, 197, 621
- Autocorrelation, *see* Correlation; Noise
- Automatic dependent surveillance, 1, 13, 650, 660, 667–669, 687
- Autofocus, SAR, 520
- Autoland, 605 ff
- Automation:
 ATM, 608, 673–675
 cockpit, 17
 nav aid, 11
See also Fault tolerance and *each nav aid*
- Autonomy, nav aid, 9
- Autopilot, *see* Flight control
- Autothrottle, 599, 675
- AV-8, 245, 636
- Availability:
 ATM, 663
 GNSS, 262–263
 GPS, 202–203, 663
 landing, 629
 Loran, 144
 nav aids, 11, 115
 WAAS, 273–274
See also Reliability; SA

- Aviation:
 air carrier, 3, 96, 656
 general, 3, 682
- Aviation System Capacity Plan, 681
- Avionics:
 architecture, 18
 bay, 3–5
 described, 15–16, 115, 691 ff
 interfaces, 691 ff
 military, 16
 partitioning, 18
 subsystems, 16
See also Packaging
- AWACS *airborne warning and control system* 290
- Azimuth:
 calculation of, 34, 281–282
 from direction cosines, 385
 free, 371
 MLS scan, 621–625
 radar, 506, 508, 558
 SAR, 513 ff
 star calculation, 556
 wander, 29, 366, 370–373
See also Heading
- B-1, 284, 450, 530
 B-2, 551
 B-52, 450
 B-58, 551
- Back azimuth, MLS, 621
- Back-course, ILS, 613
- Background light, *see* Atmosphere
- Backscattering:
 coefficient, 474–475
 Doppler radar, 452 ff
 mapping radar, 507
- Ball-bank indicator, 11, 400
- Bandwidth:
 air data, 402
 antenna, 475
 data bus, 693
 Doppler, 475
 GPS-IF, 236
 GPS P-code, 216
 Omega, 169
 radar altimeter, 493
- Band, *see* Frequency bands
- Baro-inertial, 374–375
- Barometer, *see* Altimeter
- Barometric correction, 405
- Baseband, 216
- Baseline, Loran, 153
- Batteries, 18
- Beacon:
 ATC radar, 665–667
 carrier landing, 634
 DME, 131–133
 fan, 121–122
 four-course, 11
 lighted, 11
 non-directional, 13, 120–121, 662
 radar mode, 503
 Tacan, 133
See also Interrogator; Marker beacon;
 Transponder
- Beam:
 pencil, 533, 538
 riding, 2
See also Doppler radar; Radar; Airborne
- Beam width:
 Doppler, 460 ff, 476
 ILS, 609–610, 612, 617
 MLS, 623, 625
 radar, 504
 radar altimeter, 492
- Bearing:
 to autopilot, 21
 computation, 38–40
 illustration, 30
 measurement of, 32
 relative, 39
- Bearing, gyro, 344
- Beaufort scale, 475
- Bellamy, J.C., 12
- Bends, ILS, *see* Multipath
- Bessel sidebands, 466–467
- Betelgeuse, 585
- Bias:
 accelerometer, 323, 559, 561
 clock, 83
 Doppler radar, 65, 462, 489, 559, 561
 gyro, 65, 87, 341, 345, 579
 mini, 385
 radar velocity, 528
 star sensor, 591–592
- Bins, range, 515, 519 ff
- BIT, *built-in test*:
 air data, 411, 423
 LRU, 700–701
 radar, 456, 504, 549
See also Failure detection; Fault tolerance;
 Monitor
- BITE, *built-in test equipment*, *see* BIT
- Black Sea, 175
- Blanking, Loran, 140
- BLEU, *Blind Landing Experimental Unit, UK*, 605
- Blinking, Loran, 139, 145
- Block:
 air traffic control, 12
 strapdown instrument, 356–358
- Blunder:
 navigation error, 48
 parallel approaches, 683
- Boeing aircraft:
 air data, 402, 412
 cooling, 703
 data bus, 694
 displays, 695–697
 display photos, 696
 HUD, 637
 landing systems, 605
 MLS, 626
 MTBF, 700
- Bogue, R.K., 421
- Bolter, 633. *See also* Missed approach
- Boltzmann's constant, 473
- Bomber, 5
- Bombing, radar, 503
- Boresight:
 telescope, 563, 590
See also Antenna
- Boundary layer, 578
- BPSK, *binary phase-shift keying*, 213, 278, 671
- Brazil, 152

- Bridge, compensation, 399
- Bubble level, 429
- Bubble sextant, 3, 557
- Buffalo International Airport, USA, 616
- Bug, cursor, 50
- Built-in test, *see* BIT
- Burble, 631
- Burnout protection, 245

- c, *speed of light*, 101, 223
- C, computer language, 51
- C-17, 691, 693
- C-130, 626
- C/A, *coarse/acquisition* 198
- Cables, carrier landing, 631
- CADC, *central air data computer*, 409
- Caging, gyro, 440
- Calibration:
 - accelerometer, 324
 - air data system, 408–409, 422–423
 - Doppler radar, 462, 481
 - in flight, 68, 423, 593
 - focal-plane array, 592
 - GPS, 210
 - gyro, 358
 - inertial instruments, 358
 - Loran grid, 146
 - magnetic compass, 444
 - mapping radar, 529
 - overwater, 483
 - radar PVU, 526
 - ROM, 345, 409
 - stellar-inertial, 590 ff
 - See also* Error; Kalman filter
- Cams, mechanical:
 - air data, 393
 - magvar, 438
- Canada, 12, 152, 167
- Capacity:
 - ATC system, 663, 677, 681–684
 - DME, 127–128
 - radio nav aids, 11, 116
 - PLRS, 309
 - RNAV, 649
 - runway, 690
 - Tacan, 136
 - terminal, 651
- Capricornus, 585
- Capture effect ILS, 610
- Cardioid, 119–120, 122
- Cargo aircraft, 6
- Carrier, *see* Aircraft carrier
- Carrier-phase tracking, 249 ff, 629
- Cartridge, data entry device, 21
- Caspian Sea, 175
- Cassegrain telescope, 565
- Catalog, *see* Star
- Catadioptric, 564
- CATC, *carrier air traffic control*, 631
- Category of landing:
 - Cat I, 8, 272, 663, 677, 681–684
 - Cat II, 599, 687
 - Cat III, 8, 252, 663, 687
 - Cat IIIC, 599, 605
 - See also* Airport; ILS; Landing
- Cathode ray tube display, 695
- C-band, 4–7 GHz
 - data link, 671
 - microwave landing: 621, 671
 - radar altimeter, 492
 - weather radar, 542
- CBT, *computer-based trainer*, 20, 52
- CCD, *charge-coupled device*, 553, 572–573, 596
- CCITT, *International Consultative Committee for Telephone and Telegraph*, 311
- CDI, *course-deviation indicator*, 609
 - See also* VDI
- CDMA, *code-division multiple access*, 214, 257
- CD-ROM, *compact disc read-only memory*, 21, 50, 51
- CDU, *control-display unit*, 698
- Ceiling, 597, 683. *See also* Visibility
- Ceilometer, 599
- Celestial navigation, 552 ff
 - block diagram, 580
 - calibration, 592–593
 - focal plane processing, 573
 - history, 551–552
 - manual, 2, 551
 - Moon, 586
 - moving observer, 557
 - offset gimbal, 581
 - stabilized, 578–579,
 - strapdown, 64, 563, 581–583
 - See also* Star; Telescope
- Cells:
 - PVU, 524
 - resolution, 508
 - SAR, 518
- Center:
 - ATC/ATM, 661 ff
 - CSOC, 208
 - See also* ARTCC
- Centralized, *see* Architecture
- Centrifuge, 324
- Centroid:
 - discriminant, 536
 - Doppler beam, 453, 456
 - Doppler spectrum, 462
 - optical, 574
 - radar target, 534
 - TF/TA, 535
- CEP, *circle of equal probability*, also called *circulation error probable*, 47, 561
- CERAP, *Center/Radar Approach Control*, 679
- Certification, US, 9, 253
- Cesium clock, 204
- CFAR, *constant false-alarm rate*, 540
- Chaika, *see* Chayka
- Chain:
 - Chayka, 173
 - Decca, 171
 - Loran, 139
- Changeover point, 646
- Chart:
 - airlines, 50, 52
 - for air traffic control, 642
 - airways, 647
 - analog, 50
 - approach plate, 9
 - departure, 8, 16, 49
 - digital, 16, 49–50
 - display, 211
 - en-route example, 647

- instrument, 49
- Lambert, 28
- Mercator, 16
- radar strip map, 516
- SAR, 509–510
- terrain matching, 37–38
- UTM, 28
- visual, 49
- Chayka, 173–176
- Checkpoint, *see* Waypoint
- China:
 - enroute navigation, 13
 - Loran coverage, 152, 176
- Chip:
 - GPS processing, 240
 - See also* EPROM; GaAs; MMIC; RAM; ROM; PROM; Spread-spectrum
- Chipping rate, 214, 216, 302
- Chronometer, 575
- Cicada, 178
- Circular error, *see* CEP
- CIS, *Confederation of Independent States*:
 - air traffic control, 12–13
 - Chayka, 152, 173–176
 - en-route navigation, 13
 - GLONASS, 178, 257–262
 - helicopters, 414
 - magnetic field, 437
 - Tsikada, 178
- Clearance:
 - air traffic, 645
 - delivery, 655, 657–680
 - obstacle, 648, 653
- Clearance signal, ILS, 609–610
- CLOC, *central oscillator control*, 307
- Clock:
 - air-data computer, 409
 - atomic, 204
 - drift, 190
 - error model, 82–83, 184
 - GPS, 190–192, 204, 208
 - JTIDS synchronized, 284, 286 ff, 298
 - Loran, 146
 - offset, 13, 35, 168, 184
 - Omega, 164–165, 168
 - one-way ranging error, 36
 - stability, 32, 168, 190–192
 - synchronization, 36
 - time-difference error, 36
 - See also each navaid*; Oscillator; Time definition; Time measurement
- Clock correction:
 - DGPS, 250
 - GLONASS, 262
 - GPS, 222–224
 - JTIDS drift, 286
 - passive synchronization, 287
 - relativistic, 227
- Clouds, *see* Weather
- CLR, *ILS clearance signal*, 609–610
- CMC-2012, 490
- CNES, *Centre National des Etudes Spatiales*, 202
- Coarse/acquisition code, 198
- Coast Guard, *see* USCG
- Cockpit workload, 530. *See also* Controls; Displays
- Coder, GPS, 240, 247
- Codes:
 - C/A, 214
 - Gold, 214
 - forward error correcting, 271
 - GPS spectrum, 216
 - GPS tracking, 241
 - P-, 216
 - PRN, 213–218
 - transponder, 657
 - See also* Spread-spectrum
- Coherent:
 - Doppler radar, 464
 - processing interval 540
 - video, 512
- Collision-avoidance:
 - subsystem, 16
 - taxiway, 9
 - TCAS, 684–686, 688
 - See also* Separation
- Colorado Springs, USA, 208
- Comanche helicopter, 414
- Combat, *see* Military
- Communication, air-ground:
 - ATM, 645, 658
 - aircraft carrier, 634–635
 - civil, 119
 - differential GPS, 250
 - differential Omega, 167
 - digital, 670, 687
 - HF, 660
 - integrated with navigation, 283 ff
 - JTIDS, 284 ff
 - military, 119
 - Mode-S, 667
 - oceanic, 660
 - PLRS, 311
 - satellite, 15, 670
 - subsystem, 15
 - traffic control, 669–672
- Communication, interfacility:
 - ATM, 661
 - ionospheric, 108
- Communication-navigation system:
 - en-route, 8
 - nodal, 284
 - nodeless, 283
 - post GPS, 279, 390
 - satellite, 8, 9, 15
 - terrestrial, 283 ff
 - See also* Inmarsat; JTIDS; PLRS; WAAS
- Community, navigation:
 - JTIDS, 288
 - PLRS, 300
- Commutativity, 349
- Compass:
 - astro, 446
 - gyro, 436
 - radiomagnetic, 426
 - See also* Magnetic compass
- Compensation:
 - air data, 402 ff
 - antenna stabilization, 134
 - GPS frequency, 194
 - magnetic, 438
 - meatball, 634
 - vertical gyroscope, 434

- Compensation (*cont'd*)
 See also Calibration; Errors; Kalman filter;
 Motion compensation
- Compression, *see* Pulse
- Computer:
 air data, 409-411
 analog, 400, 438
 architecture, 412-413
 centralized, 18
 decentralized, 18
 distributed, 412
 federated, 93-96
 iteration rate, 353, 411, 539
 microprocessor, 247
 parallel, 540
 See also each navaid
- Conductivity, *see* Earth
- Cone of silence, 120
- Confidence, *see* Quality
- Configuration control, software, 51
- Conflict, ATC:
 alert, 678
 prediction, 679
 TCAS, 685
- Conical scan, 634
- Coning, 353, 358-359
- Conning, 1
- Constellation:
 GLONASS, 262
 GPS, 200
 star, 584
- Continuity, 263
- Continuous wave Doppler, 465-472
- Control area, *see* Airspace
- Controller:
 hand, 18
 human ATC, 655 FF
- Controls:
 cockpit, 17
 fly-by-wire, 18
 subsystem, 18
 See also Display, Cockpit; Flight control
- Control segment, GPS, 179, 207
- Control tower, 14
- CONUS, *continental United States*, 202, 252, 269, 273
- Converging runway display aid, 684
- Convolutional code, 213-218
- Cooling, *see* Temperature
- COP, *changeover point* 646
- Coordinates:
 celestial, 553-555
 direction cosines, 27, 349 ff
 Doppler radar, 454, 485
 Earth-centered, 26
 geodetic, 27
 GLONASS, 262
 inertial, 26-27, 365-367
 JTIDS, 288
 map grid, 28
 MGRS, 28, 302
 radar, 527
 rotating, 365-367
 tangent plane, 29
 transverse pole, 28
 wander azimuth, 27, 370 ff
 See also MGRS
- Coriolis acceleration:
 defined, 368 ff
 inertial error, 61
 in vertical gyro, 435
- Corner post, 659
- Correlation:
 codeless, 198
 coefficient, 45
 Doppler, 462, 477
 GPS, 214, 216, 277
 GPS code, 240
 loss, 217
 stellar inertial, 561-562
 terrain-matching, 37
 See also Covariance matrix; Spread-spectrum
- Correlation distance, 146
- Correlation time, Doppler, 462, 477
- Correlator, 240, 247, 516
- COSPAS, Russian acronym for search and rescue satellite, 16
- Cost:
 flying time, 675
 GNSS, 664
 GPS user charges, 15
 inertial navigator, 313
 military avionics, 16
 radar, 503-504
 tradeoffs, 8
 see each navaid
- Counterpoise, 110-111, 125
- Course-line computation:
 block diagram, 22
 description, 38-41
- Covariance matrix:
 defined, 374-375
 information, 564
 system error, 46
 See also Error; Kalman filter
- Coverage, geographic:
 Chayka, 174
 gaps, 3
 GPS, 200-204, 273
 Loran, 152
 navaids, 115
 tradeoffs, 11
- CPA, *closest point of approach*, 685
- CPE, *circular probable error*, *see* CEP
- CPI, *coherent processing interval*, 540
- CPU, *central processing unit*, 409
- Crab, landing, 603
- CRDA, *converging runway display aid*, 684
- Crew:
 ATM responsibilities, 658, 660
 See also Display; Human navigator; Trainer;
 Landing
- Cross-correlation, *see* Correlation
- Cross-coupling:
 accelerometer, 320
 gyro, 325
- Cross-pointer, 609
- Cross-track velocity:
 illustrated, 30
 Doppler, 451, 459
- Cross-wind:
 drift, 30
 landing, 603 ff
- CRPA, *controlled reception pattern antenna*, 230

- CRS, *ILS course signal*, 610
 CRT, *cathode ray tube*, 695
 Cryptographic:
 GPS security, 198
 key, 235
 security, 300
 Crystal, *see* Clock
 Cs, *cesium*, 204
 CS, *see* Control Segment, GPS
 CSB, *ILS carrier-with-sidebands signal*, 609
 CSOC, *consolidated space operations center*, 208
 Cursor control, 509, 698
 CW, *continuous wave*, 155, 465
 Cycle slip:
 GPS, 630
 Omega, 168
 D, *Bellamy Drift*, 12
 Damping:
 accelerometer, 320–321
 compass needle, 440
 Doppler-inertial, 65, 479
 gravity sensor, 428
 leveling loop, 383–384
 vertical gyro, 432–433
 Data bus:
 air-data computer, 409
 avionics, 18
 controller, 691
 fiber optic, 693
 GPS, 234–235
 high speed, 693
 inter-subsystem, 18, 691–694
 MLS, 626
 STANAG-3838, 693
 See also ARINC; MIL-STD-1553
 Data-entry device, 21
 Data link:
 ATC, 665, 669
 carrier landing, 634–635
 future, 687
 satellite, 671
 See also Communication; Mode-S
 Data message, GPS, 218 ff
 DBS, *Doppler beam sharpening*, 504
 DDM, *difference in depth of modulation*: 609
 Deadband:
 accelerometer, 323
 laser gyroscope, 341
 Dead-reckoning:
 defined, 2
 Doppler radar, 31
 equations, 29–32
 flat Earth, 31
 gyroscopes, 426 ff
 illustration, 30
 JTIDS, 290
 in multisensor system, 55
 Omega, 3, 155–171
 sensors, 56
 with wind, 31
 Dead zone, *see* Deadband
 Decca, 171–173
 Decentralized, *see* Architecture
 Decision height:
 ATC, 654
 defined, 8, 598, 654
 See also Approach, Precision
 Deck motion, 631
 Declination:
 astronomical, 553
 magnetic, 437
 Decrab, 603 ff
 Defect, static, 394, 396
 Defense Mapping Agency, US, 197, 208
 Deflection of the vertical, 25, 98, 188–190
 Degrees of freedom:
 gyroscope, 325, 344
 platform, 361
 Delay:
 air-data pneumatics, 412
 air traffic, 681
 alarm, 266
 compass, 440
 data bus, 694
 Doppler radar, 479
 group, 194
 ionospheric, 225–226, 249
 PLRS, 305
 TCAS, 686
 tradeoff, 10
 traffic model, 690
 tropospheric, 196
 See also Latency
 DMA, *Defense Mapping Agency*, US, 197, 208
 Departure:
 controller, 655
 description, 7, 657
 routes, 659
 terminal VOR, 646
 Depth of focus, SAR, 518
 Descent, rate of:
 carrier landing, 631
 land landing, 603
 Detector, *see* Sensor
 Deviation, magnetic, 438
 DF, *see* Direction finder
 DGPS *differential GPS*:
 accuracy, 14
 for approach, 251–252, 628–630, 638
 corrected pseudorange, 250
 description, 248–253
 kinematic, 252
 landing, 663
 RTCM-SC104, 250
 runway surface, 680
 standard message, 250–251
 DGRF, *Definitive Geomagnetic Reference Field*, 437
 DH, *see* Decision height
 Diego Garcia Island, 208
 Differential:
 carrier phase, 252
 GPS, 248–253
 Loran, 146
 Omega, 167
 Diffraction, 565
 Dipole:
 antenna, 101–102
 magnetic, 437
 Directional gyroscope, 444–446
 Direction finder, 112
 Direction cosines:
 azimuth from, 385

- Direction cosines (*cont'd*)
 inertial mechanization, 342 ff, 354 ff, 371
 JTIDS, 294
 latitude-longitude from, 372
 multisensor software 90
 numerical example, 52-53
 strap-down, 350-352
- Direction finder:
 airborne, 117
 ground, 116
 radio, 112
- Directivity, antenna, 101
- Direct ranging, *see* Ranging
- Dispatch:
 airline charts, 50, 676
 computer, 21
 FMS, 676
 inoperative avionics, 703
- Display, cockpit:
 ATC, 673-675
 avionics, 17
 ball-bank indicator, 400
 block diagram, 22
 cathode ray tube, 695
 CDI, 609
 CDU, 698
 conventional, 426, 696
 cross-pointer, 609
 DME, 608
 EICAS, 695
 eight ball, 426
 flat panel, 695
 glass, 426-428
 HSI, 426-427, 695
 liquid crystal, 695
 marker beacon, 618-619
 manual target-finding, 506-507
 map, 17, 50
 map radar, 505, 507, 549
 micromachined sensor, 429
 multifunction, 695
 PFD, 696
 radar altimeter, 495
 radio-magnetic compass, 426
 speech, 699
 VDI, 613
 VOR, 126
 VSI, 426-427
 weather radar, 540
See also Display, Map; HMD; HUD
- Display, traffic control, 673-675, 684
- Distance calculation:
 flat Earth, 39
 spherical Earth, 40
- Distance measuring equipment, *see* DME
- Diurnal correction:
 Loran, 142
 Omega, 160
 electron density, 194
- Diversity, radio propagation, 111
- DMA, *see* Defense Mapping Agency
- DME:
 block diagram, 129
 capacity, 127-128, 132
 duty cycle, 132
 identifier, 132-133
 landing, 627-628
 with MLS, 621
 receiver, 128-131
 recovery time, 130
 signal-in-space, 127
 steering to, 42
 on taxiway, 604
 transmitter, 131-133
- DME/N, 628
- DME/P, 621, 627-628
- DO-160, 700
- DoD, *Department of Defense*, US, 643
See also Military; United States
- Doppler, Christian, 451
- Doppler navigator:
 block diagram, 452
 with GPS, 183, 189, 218
 in multimode radar 539-540
 system error, 488-490
 test results, 489
See also PVU; Multisensor navigation
- Doppler radar:
 bandwidth, 475
 beam configuration, 454-457
 boresighting, 486
 calibration, 48-483
 components, 464
 continuous-wave, 465-466
 errors, 477-490, 501
 FM/CW 466-469, 474
 frequency tracker, 469-472, 476
 heading reference, 446, 498
 homodyne, 465, 467
 installation, 486
 maneuver error, 485
 mountain paradox, 453-454
 sea current, 481
 signal/noise, 472-474
 smooth-earth paradox, 453
 spectrum, 460 ff, 479, 481-482
 stabilization, 459-460, 474, 485-486
 terrain bias, 481
 transmitter frequency, 463
 velocity sense, 465, 471
See also Antenna; Backscatter; Doppler navigator; Helicopters; Multisensor navigation; Noise; Oscillator; Radome
- Doppler shift:
 air data, 419
 beam sharpening, 504, 513
 described, 451-453
 drift angle, 31
 GPS, 240
 radar, 451 ff
 radar filter, 514 ff
 SAR radar, 523
See also Doppler radar
- Doppler velocity:
 measurement of, 449 ff
 from multimode radar 538-539
See also PVU
- Doppler VOR, 126-127
- Dorne & Margolin, 245
- Douglas aircraft:
 antenna farm, 4
 displays, 699
 HUD, 637

- Downconverter, 493, 546
 Downwash, 413, 418
 DPSK, *differential phase-shift key*, 626, 670
 Drag, orbital, 188
 Drift, gyro:
 aniso-elastic, 346
 bias, 341, 345–346
 coning, 353, 358–359
 directional gyro, 445
 in error analysis, 376
 historical, 325
 magnetic, 342, 346
 mass unbalance, 346
 math model, 341–342
 optical gyro, 331, 340–341
 strapdown, 325, 348
 temperature-dependent, 341, 346
 vertical gyro, 432
 Drift angle:
 illustration, 30
 measured by Doppler radar, 459
 pressure pattern, 12
 Drift sight, 12, 30
 Drone, *see* UAV
 Duplex data bus, 691
 Duty cycle, DME, 132
- E2A, 284, 290, 450
 E3, 284, 290, 450
 Earth:
 conductivity, 104, 141, 143, 161
 coordinate frame, 26–29, 365 ff
 dielectric constant, 104
 dimensions, 23–25
 gravitation, 187, 223
 magnetic field, 437–438
 orbit, 590
 polar wander, 389
 radar backscatter, 474
 rotation rate, 23, 188, 365, 554
 VLF anisotropy, 161
 See also Atmosphere; Ionosphere; Troposphere
 ECEF, *Earth-centered, Earth fixed*, 26, 184, 212
 ECCM, *electronic counter-countermeasures*, 300, 538
 ECD, *envelope-to-cycle difference*, 140
 ECI, *Earth-centered inertial*, 26–27
 Eccentricity, orbit, 186, 200
 Ecliptic, 553
 EEPROM, *electrically erasable PROM*:
 air data, 409
 stored program, 51
 Effective radiated power, 103
 Efficiency, quantum, 572, 574
 EFGS, *end-fire glide slope*, 617
 EGNOS, *European Geostationary Navigation Overlay System*, 268
 EHF, *extremely-high frequency*, 100
 EI, Earth ionosphere, 161
 EICAS, *engine indicator and crew alerting system*, 695
 Eight-ball indicator, 426
 EIRP, *effective isotropic radiated power*, *see* ERP
 Electric power, *see* Power, Radiated; Power consumption
 Electrolytic level, 429
 Electromagnetic interference, *see* EMI
- Electronic countermeasures, 17
 Elevation angle:
 line of sight, 34
 during GPS pass, 640–641
 MLS scan, 624–625
 star calculation, 556
 Ellipse, orbital, 186
 Ellipsoid, reference, 23
 See also Earth
 ELT, *emergency locator transmitter*, 16
 EMI, *electromagnetic interference*:
 avionics, 16, 276–278
 data bus, 693
 GPS near-far, 206, 232, 277
 radar, 538
 Engine control, 16
 Engineer, flight, 19
 En-route:
 navigation, 7
 traffic control, 658–659, 677–679
 Environment:
 anti-jam, 232
 GPS space, 204
 HIRF, 18
 mechanical, 3, 18
 thermal, 3, 346
 See also EMI; Lightning; Vibration
 Ephemeris:
 star catalog, 556, 563, 590
 errors, GPS, 249
 GLONASS, 261
 GPS, 223–224
 WAAS, 271
 EPLRS, *enhanced PLRS*, 310
 Epoch, 216, 584
 EPROM, *erasable programmable read-only memory*, 51, 409
 Equinox, vernal, 186, 584
 Erection, v-gyro, 431–432
 Ergodic statistics, 44
 ERP, *effective radiated power*, 102
 Error, component:
 accelerometer, 322, 560
 beam direction, 480
 clock, 82–83, 255
 coning, 353, 358–359
 lever arm, 359
 mechanical gyroscope, 345–346, 560
 optical, 574 ff
 optical gyroscope, 340–342
 PVU, 525
 sculling, 359
 star angle, 552
 Error, subsystem:
 air data, 418, 422
 baroinertial altitude, 374, 378
 DGPS, 251
 DME, 132
 differential, 114
 direction finder, 119
 Doppler fluctuations, 477–478
 Doppler radar, 497–498
 glide slope, 616–619
 GPS, 198, 208, 227, 253–257
 GPS velocity, 255
 inertial, 373, 376 ff
 JTIDS RelNav, 290, 297–299

- Error, subsystem (*cont'd*)
 localizer, 619-620
 Loran, 52, 143
 magnetic compass, 438 ff
 mapping radar, 529
 obstacle clearance, 652-653
 Omega, 156, 165, 166-167
 PLRS propagation, 298-299, 310
 radar altimeter, 495
 radar velocity, 527-528
 step, radar altimeter, 495
 Tacan, 136
 vertical gyro, 433-436
 VOR/DME, 126, 647
 warm up, 381
See also each navaid; Error, Budget; Error, System
- Error, system:
 absolute, 114
 along track, 489
 autoland, 607
 cross-track, 489
 description, 44-48
 en-route, 8
 instrumentation, 115
 mean, 45-46
 mean square, 45-46
 navigation system, 299, 458
 principal axes, 45
 relative, 114
 repeatable, 114
 stellar-inertial, 561-562
 system use, 44
 terminal area, 7
 test data, 44-48
 3-dimensional, 48-49, 201-202
 tradeoffs, 9
 2-dimensional, 48-49, 201-202
 uncorrelated, 49
 vertical channel, 253
 wild points, 480
See also Covariance; Flight technical error
- Error budget:
 air data, 408
 Doppler radar, 477-487
 GPS, 253-257
 inertial, 377-379
 JTIDS, 297-298
 radio link, 103-104
 SAR, 522
- Error covariance matrix, 75
 Error rate, PLRS, 309
 ESA, *electronically scanned array*, 546
 Escape maneuver, 686
 Estimator, *see* Filter
 ETR, *external time reference*, 286
 Euler angles, 349
 EUROCAE, *European Organisation for Civil Aviation Equipment*:
 altimetry, 727
 description, 19, 608
 GPS, 719
 ILS, 608
 marker beacon, 619
 MLS/ILS, 621, 735
 specifications, 19, 705, 707, 711
- Europe:
 Geostationary Overlay, 268
 ILS interface, 620
 Loran chain, 152
 traffic control, 12, 167, 687
 Exciter, radar, 539, 548
- 4, 284, 538
 F-15, 284, 402, 691, 695
 F-16, 402
 F-18, 245, 538, 633
 F-22, 691, 693
 F-104, 421
 F-111, 450, 530
 FA, *final approach*, 628
 FAA, *Federal Aviation Administration*, US:
 Advisory Circulars, 734
 airport lights, 600
 airport capacity, 681
 data link, 670
 display, 694
 GPS, 235, 251
 ILS, 608
 landing categories, 606
 Loran regulations, 175
 Omega regulations, 168
 overwater, 3
 required navigation, 663
 TCAS, 684-686
 terminal facilities, 679
 traffic publications, 736
 TSOs, 705, 728
 WAAS, 268, 271
 weather, 672
 FAA, *Technical Center*, 275
 FADS, *flush air-data system*, 422
 FAF, *final approach fix*, 600
 Fail-safe, *see* Fault tolerance
 Failure detection:
 Loran, 139
 subsystem, 16
 WAAS, 272-273
See also BIT; Fault-tolerance; Monitor; RAIM; Safety-critical
- Fan beam:
 airborne radar, 546
 marker beacon, 121-122
 microwave landing, 621-622
 Fan marker, 121-122
 FANS, *Future Air Navigation System*:
 GPS, 279
 oceanic, 13, 660
 FAR, *Federal Aviation Regulations* (US)
 Faraday Effect, 333
 Fault, *see* BIT; Failure detection; Fault tolerance; Monitor
 Fault tolerance:
 computation, 18
 FDE, 272
 GPS monitor, 210
 GPS spacecraft, 205-206
 landing, 599
 MLS, 627
 quadruple bus, 692
 strapdown IMU, 357
 WAAS, 272-273

- See also BIT; Category III; Failure detection; Monitor; RAIM; Safety-critical
- FCS, *flight control system*
- FDE, *fault detection and exclusion*, 264
- FDMA, *frequency division multiple access*, 257
- FEC, *forward error correction*, 271
- Federal Aviation Administration (US), see FAA
- Federal Radionavigation Plan (US), 136, 145, 200, 662
- Federated, 93–96
See also Architecture
- FFT *fast Fourier transform*:
radar, 497, 540
SAR, 519
target detection, 540
- Fiberoptics:
gyro, 336
interconnects, 548, 693
- Field of view:
optical, 566 ff
radar, 508
- Field stop, 565
- Filter:
anti-aliasing, 247
bank, 546, 548
baro-inertial, 375
Doppler inertial, 67
Doppler radar, 469–470
GPS-IF, 236
gyrocompass, 385
leakage elimination, 465
least squares, 70–72
leveling, 383
Loran notch, 151
marker beacon, 618
matched, 285, 574
multisensor, 55 ff
notch, 151
PLRS tracking, 307–308
radar beam sharpening, 513–514
radar matched, 539
recursive, 70–72, 75
SAR, 515 ff
satellite triplexer, 206
SAW, 236
sensor errors, 70
transfer alignment, 387
vertical gyroscope, 433
weighting functions, 71
See also Kalman filter; Multisensor navigation
- Final approach segment, 654. See also Approach
- FIR, *flight information region*, 680
- Fire control, 16, 413
- Fix:
absolute, 114, 283
arrival, 659
automatic radar, 509–511
celestial, 2, 551
differential, 114
final, 600, 653
holding, 658
hyperbolic, 164
inertial, 69, 313–314
initial, 600, 653
intermediate, 653
metering, 658
Omega, 162–165
radar manual, 503
radar reference, 505
radar update, 506
radio, 32, 112
rho-rho, 113–114
rho-theta, 113
semiautomatic radar, 509 ff
Tercom, 37–38
theta-theta, 113
- FL, *flight level*, 644
- Flare maneuver:
carrier landing, 631
described, 603–607
dispersions, 607
equations, 603
guidance, 606
- Flight control system:
accelerometer, 426
bank angle, 41–42
carrier landing, 634
fail-operational, 599, 637
fail-passive, 599, 637
landing, 597, 603–607, 609
subsystem, 1, 15
terrain following, 530, 536–538
- Flight-critical, see Safety-critical
- Flight director, ILS, 599
- Flight level, 644
- Flight management system, 16, 409, 670, 675, 688, 698
- Flight path angle, 30, 375
- Flight plan, ATC:
contract, 645
IFR, 656
processing, 678
VFR, 657
- Flight rules, see IFR; VFR
- Flight service station, 32, 656, 680
- Flight strips, 678, 680
- Flight technical error, 44, 116, 254, 647, 653
- Flight test, see each *navaid*; Test
- FLIR, *Forward-looking infrared detector*, 530, 636
- FLOLS, *Fresnel Lens Optical Landing System*, 632–634
- Flow, ATC, 658
- Flux gate, 440–441
- Fly by wire, 18
- FMC, *flight management computer*, see Flight management system
- FM-CW, *frequency modulated continuous wave*:
altimeter, 493–497
Doppler radar, 466–469
- FMS, see Flight management system
- f/number, telescope, 566
- FOC, *full operational capability*, 175
- Focal length, 565
- Focal plane, optical:
defined, 565
sensor array, 573–574, 637
- Focus, radar, see SAR
- FOG, *fiber-optic gyro*, 336 ff
- Forrestal, 631
- Foucault pendulum, 61
- Formation flight, 18
- Fortran, 51
- Four-dimensional navigation, 16
- Frame, GPS, 220

- Framing pulses, 665
 France, 11, 176, 202, 437
 Free azimuth, 371
 Free flight, 8, 688
 Frequency, operating:
 bands, 100–101
 Chayka, 173
 Decca, 171
 direction finder, 120
 DME, 127
 Doppler radar, 463
 glide slope, 609
 GLONASS, 258
 GPS, 198, 206
 JTIDS, 285
 laser gyroscope, 331
 localizer, 609
 Loran, 139
 marker beacon, 121, 609
 MLS, 621
 Omega, 157
 PLRS, 300
 radar, 538
 radar altimeter, 492
 Tacan, 133
 VOR, 122
 weather radar, 542
 See also each navaid
 Frequency measurement, Allan variance, 190–192, 208
 See also Time measurement
 Frequency, plasma, 193
 Frequency stability, 192
 Frequency tracker, *see* Tracker, Electronic
 Fresnel lens, 633
 Front course, ILS, 613
 FRP, *see* Federal Radionavigation Plan
 FRPA, *fixed radiation pattern antenna*, 245
 FSS, *flight service station*, 656, 677
 ft, *foot*, meter equivalent, 25
 FTE, *see* Flight technical error
 Fuel usage, 656, 675–676
 Future trends, *see last section of each navaid chapter*
- g, *gravity unit*
 GA, *ground antenna*, 208, 212
 GaAs, *gallium arsenide*, 493, 546, 548
 Gain:
 antenna, 101
 scheduling, 606
 Gatwick Airport, 597
 Gaussian:
 distribution, 46–47, 478
 Doppler noise, 460
 MLS delay, 628
 radius of curvature, 25, 40
 GCA, *ground-controlled approach*, 6
 GDOP, *geometric dilution of position*:
 defined, 201
 described, 48–49, 113, 115
 equations, 48–49
 GPS, 201
 JTIDS, 298–299
 Loran, 143–144, 153
 Omega, 166
 GEC Avionics, Inc., 419
 General aviation, 3, 175
 GEO, *geostationary orbit*, 268–269
 Geodesy, 23–25
 Geological Survey, US, 437
 GEOMAG, 437
 Geometric dilution of precision, *see* GDOP
 Geopotential, *see* Gravity
 Geostationary orbit, 202, 268–269
 GES, *ground earth station*, 269
 GHA, *Greenwich hour angle*, 554–556
 GHz, *gigahertz* = 109 Hz
 Gimbal:
 antenna, 527
 gyro, 344
 platform, 361
 telescope, 63, 579, 583, 591
 See also Platform, Inertial
 Gimbal lock, 361
 Glide path angle:
 carrier, 631
 land, 602
 Glide slope:
 aircraft carrier, 631
 antenna, 614–617
 bends, 619–620
 capture effect, 614
 description, 614–617
 end-fire, 617
 modulation, 624–625
 obstacles, 654
 point of intercept, 654
 stabilized, 634
 waveguide, 616
 Global Navigation Satellite System, *see* GNSS
 Global Orbiting Navigation Satellite System, *see* GLONASS
 Global positioning system, *see* GPS system: GPS receiver
 GLONASS Russian *Global Orbiting Navigation Satellite System*:
 cost, 15
 description, 257–262
 landing, 628, 662
 outlook, 14–15, 175, 687
 GMV, *ground moving vehicles*, 545
 GNSS, *Global Navigation Satellite System*:
 availability, 262–263
 description, 178
 GPS, 235, 687
 integrity, 262–263
 landing, 662
 over ocean, 661
 RNAV, 649
 required accuracy, 263
 Goniometer, 117, 119, 123
 GPS hybrids, *see* Multisensor navigation
 GPS receiver:
 AGC, 246
 antenna requirements, 230
 block diagram, 231, 237, 244
 on a card, 235–238
 commercial, 235–242
 description, 229–248
 downconverter, 232, 238
 dual-frequency, 194–195
 filtering, 236, 242, 245

- frequency plan, 233
- IF section, 233–234
- MAGR, 243–247
- oscillator, 232–233
- signal processing, 234, 242
- See also* Antenna
- GPS system:
 - accuracy, 253–257
 - A-S/SA, 198, 235, 248
 - for ATC, 663
 - Category I approach, 254
 - constellation, 200, 210
 - control segment, 208–209
 - cost, 15
 - description, 179 ff
 - ECEF calculation, 280
 - en-route, 7
 - errors, 227–228
 - for free flight, 688
 - measurements, 226–227
 - military use, 5
 - navigation solution, 228–229
 - outlook, 175
 - over ocean, 650
 - range calculation, 33–35, 180–183
 - runway surveillance, 605
 - signal-in-space, 213–218
 - sole means of navigation, 235, 687
 - spares, 207
 - spacecraft, 204–206
 - traffic control, 687
 - user charges, 15
 - See also* Clock; Codes; DGPS; GPS receiver; Integrity;
 - Message navigation; Multisensor navigation; RAIM
- GRASS, *Geographical Resource Analysis Support Group*, 50
- Gravitation, 35, 187, 223
- Gravity, 23
- Great circle, 40
- Greenwich:
 - hour angle, 554, 576
 - meridian, 26, 554
- GRI, *group repetition interval*, 139, 149
- Ground controller, ATC, 655, 680
- Ground wave:
 - attenuation, 105
 - one-way ranging, 35–36
 - propagation, 104–106
 - range calculation, 35
 - time-differencing, 36–37
- GT *ground transmitter*
- Guard sampling, 151
- Guidance, defined, 1–2
- Gulf Stream, 484
- Gunfire aiming, 17, 413
- Gunn diode, 490
- Gust, *see* Wind
- Gyrocompass:
 - airborne (erroneous), 436
 - inertial, 384–386
 - marine, 313
- Gyroscope, directional:
 - description, 444 ff
 - backup, 446
 - gravity sensor, 444
 - performance, 445
 - slaving, 445–447
- Gyroscope, fiberoptic:
 - closed loop, 339
 - description, 326, 336 ff
 - errors, 340–341
 - modulation, 338–339
 - resets, 339
- Gyroscope, mechanical:
 - description, 324, 342ff
 - electrostatic, 325
 - floated, 325
 - hemispherical resonator, 348
 - history, 325
 - micromachined, 347
 - simple, 427 ff
 - single-degree-of-freedom, 325
 - testing, 347
 - tuned rotor, 325, 343–347
 - two-degree-of-freedom, 325, 343 ff, 434, 444
 - See also* Gyroscope, Directional; Gyroscope, Vertical
- Gyroscope, ring laser:
 - cavity, 327, 331–332, 335
 - description, 326 ff
 - dither, 331, 333
 - error model, 345
 - finesse, 329
 - gas mixture, 332
 - lock-in, 330
 - mirrors, 327, 331
 - mode hops, 332
 - multioscillator, 326, 333 ff
 - performance, 340–341
 - pseudoconing, 333
 - rate biasing, 331
 - scale factor, 328
 - two-mode, 327
 - vibration, 331–333
 - weight, 340
- Gyroscope, vertical:
 - compensation, 433–434
 - description, 429 ff
 - dynamic response, 431–436
 - erection, 431
 - performance, 430, 432
- Hall Effect, 443
- Hamming code, 221
- Hand-off, ATC, 658, 660
- Hand-over word, 218
- Hard iron, 438
- Harmonics:
 - gravitational, 189
 - magnetic field, 437
- Harrier, *see* AV-8
- Hawaii, 208
- Hawkeye, 290
- HCG, *half-cycle generator*, 147
- HDOP, *horizontal dilution of position*:
 - description, 49
 - for GPS, 201, 253
- Heading:
 - best available, 29
 - gyro, 444–446
 - illustration, 30
 - inertial measurement, 371

- Heading (*cont'd*)
 magnetic, 30, 440-443
 reference for Doppler radar, 450, 488
 toward target, 34
 true, 30
See also Azimuth
- Heading reference, *see* Gyroscope, directional;
 Inertial navigator; Magnetic compass
- Head-up display, *see* HUD
- Heat removal, *see* Temperature
- Heave, deck, 631
- Helicopter:
 air data sensors, 413 ff
 Doppler radar, 72, 89, 450, 469, 502
 military, 6
 naval, 636
 operational, 6
- Heterodyne:
 Doppler radar, 465
 mapping radar, 512
- HF, *high frequency*, 100
- HF/DF, *high-frequency direction finder*, 11
- HG9550, 498
- HIRF, *high intensity radiated fields*, 18
- History of nav aids, 11-13
See also each nav aid; Time measurement
- HMD, *helmet-mounted display*, 696
- Holding:
 aircraft carrier, 631
 ATC, 658
- Homing, 119
- Homodyne radar, 465, 467
- Honeywell:
 air data, 402-403
 inertial, 357
 radar altimeter, 495
- Honolulu, 681
- Houston, 681
- HOW, *handover word*, 218, 221
- HPA, *high-power amplifier*, 270
- hr, *hour*
- HRG, *hemispherical resonator gyro*, 348
- HSDB, *high-speed data bus*, 693
- HSI, *horizontal situation display*, 691
- HUD, *head-up display*, 637, 696-698
- Human navigator, 504-505, 647
- Hyperbolation, 298
- Hyperbolic navigation, 138 ff
 reduction of fix, 162-166
See also Decca; Loran; Omega
- Hypersonic:
 aircraft, 3
 air data, 421-422
See also Supersonic
- Hysteresis, *accelerometer*, 321
- Hz, Hertz = cycle/second
- I, *in-phase*, 234
- IA, *initial approach*, MLS, 628
- IAF, *initial approach fix*, 600, 653
- ICAO, *International Civil Aviation Organization*:
 airport lights, 600
 annexes, 733
 approach, 600
 DME, 132
 FIR, 680
 GNSS, 178, 279
- ILS, 608, 620
- ILS indicator, 609-610
- interfacility communication, 661
- landing categories, 598, 662
- microwave landing, 621, 628
- Mode S, 661
- publications, 19, 737
- standard atmosphere, 644
- traffic control, 643
- vertical separation, 651
- VOR, 122
- WAAS/SBAS, 268
- ICD, *interface control document*, 261
- ICD-GPS-200B-PR, 212
- Icing:
 helicopter, 416
 probes, 396
- ICNIA, *integrated communication, navigation, and identification: avionics*, 96
- ICNIS, *integrated communication, navigation, and identification system*, 96
- ICO, *intermediate circular orbit*, 279
- ICW, *interrupted continuous wave*, 465
- ID, *identification*, 675
- IDENT, *identification code*, 665
- Identification point, 509, 517
- IEEE, *Institute of Electrical and Electronics Engineers*, 725
- IF, *intermediate fix*, 653
- if, *intermediate frequency*
- IFR, *instrument flight rules*, 9, 598, 645, 677
- IFRB, *International Frequency Registration Board*, 258
- IFOG, *interferometric fiber-optic gyro*, 336 ff
- IGRF, *International Geomagnetic Reference Field*, 437
- IIP, *ionospheric intersection point*, 225
- ILS, *instrument landing system*, 608-620
 aircraft carrier, 634-636
 bends, 619
 error, allowed, 611
 limitations, 619
 low-visibility landing, 599
 microwave, 620-627
 military use, 6
 monitors, 608
 paired frequencies, 609
 portable, 627
 Russian, 13
 signal-in-space, 609
 usage, 652-654
See also Glide Slope; Localizer; MLS
- IM, *inner marker beacon*, 618, 654
- IMA, *integrated modular avionics*, 96
- Image:
 optical, 565 ff
 radar, 505 ff
See also Display
- IMC, *instrument meteorological conditions*, 9, 598, 651, 657
- IMU, *inertial measurement unit*, *see* Inertial navigator
- Inclination of orbit, 185
- Index of refraction, *see* Atmosphere; Ionosphere
- India:
 Loran coverage, 152, 176
 Omega coverage, 167

- Indian Ocean, 13, 270
- Indonesia:
 - air traffic control, 13
 - Omega coverage, 167
- Inertial navigator:
 - AHRS, 389
 - alignment, 379–388
 - cost, 313
 - errors, 358–360, 376–379,
 - history, 313–314
 - horizontal mechanization, 368–373
 - for landing, 14, 263
 - limitations, 389
 - military use, 5
 - over ocean, 650
 - SAR processing, 519
 - SAR stabilization, 511
 - sole means, 661
 - strapdown, 356–358
 - system, 314–317
 - system specification, 349, 364
 - throwaway, 390
 - vertical mechanization, 373–375
 - wander azimuth, 366
 - weight, 317
 - See also* Accelerometer; Alignment; Gyroscope; Multisensor navigation; Platform
- Inertial navigation hybrids, *see* Multisensor navigation
- Inertial space, defined, 26–27
- Information, defined, 563–564
- Infrared, *see* Optical; Sensor; Star
- Initial conditions:
 - dead-reckoning, 29
 - inertial navigator, 379–388
 - Kalman filter, 76–77
 - time, 575
- INMARSAT, *International Maritime Satellite Organization*, 268–271
- Input-output, computer, *see* Data bus
- INS, *inertial navigation system*, *see* Inertial navigator
- Installation:
 - air data, 393–394
 - antennas, 4, 626
 - avionics, 4, 703
 - Doppler radar, 486
 - EMI, 703
 - HUD, 697
 - inertial platform, 356–357
 - JTIDS, 297
 - maintenance, 700
 - radar mounting, 528
 - stellar-inertial, 577
- Instrument approach procedure, 652, 655
- Instrument departure procedure, 655, 657
- Instrument flight rules, *see* IFR
- Instrument landing system, *see* ILS
- Instrument meteorological conditions, *see* IMC
- Integrated navigation systems, *see* Multisensor navigation systems
- Integrity, navaid:
 - ATC, 663
 - defined, 11, 115
 - GNSS, 262–263, 687
 - GPS receiver, 230
 - GPS system, 663
 - landing, 605
 - Loran, 145
 - See also* Fault tolerance; RAIM; WAAS
- Interdiction, 5
- Interfaces, intersubsystem, *see* Data bus
- Interference, *see* EMI
- Interferometer:
 - fiberoptic, 336–337
 - gyro, 326, 329, 337
 - radar, 538
- International Association of Geomagnetism and Aeronomy, 437
- International Civil Aviation Organization, *see* ICAO
- International Frequency Registration Board, 258
- International traffic control, 13, 660
- Interrogator:
 - ATC radar, 665
 - DME, 127
 - JTIDS, 287
 - Tacan, 133
 - See also* Beacon; Transponder
- Interrupted CW Doppler, 465
- Intersection, chart, 43
- I/O, *input-output*, *see* Data bus
- IOD, *issue of data*, 250
- IODC, *issue of data clock*, 223
- IODE, *issue of data ephemeris*, 224
- Ionosphere:
 - best path, 108
 - correction, 213
 - D, E regions, 161
 - delay model, 193–194, 225–226, 249
 - dual-frequency correction, 195
 - electron density, 194
 - GPS correction, 195, 227
 - Omega propagation, 161
 - refraction, 106, 192–194
 - scintillation, 195
 - skip distance, 107
 - sunspot cycle, 161
 - windows, 109
- IOR, *Indian Ocean Region*, 270
- IP, *identification point*, 509, 517
- I/Q, *in-phase/quadrature*, 528
- Iridium, 279
- Irradiance, star, 567
- IRS, *inertial reference system*, 263
 - See also* Inertial navigator
- IRU, *inertial reference unit*, 650
- Island, aircraft carrier, 631
- ISO, *International Standards Organization*, 672
- Isodops, 459, 482
- Isolation:
 - gimbals, 362
 - inertial sensor, 357
 - transmitter/receiver, 467
- Isotropic radiator, 104
- Iterative solution, 43, 70–72, 181–184
- ITT Aerospace, 205
- JAA, *Joint Aviation Authority*, Europe, 608
- Jamming:
 - altimeter, 498
 - GPS, 230
 - military, 300
 - stellar, 551
- Janus beams, 454, 480, 500, 523

- Japan, Loran coverage, 152
 Jet route, 646-647
 Jitter, PPI, 498
 Jovial, 51, 539
 JPL, *Jet Propulsion Laboratory*, USA 208
 JPO, *joint project office*, 197
 JSTARS, *joint surveillance target attack radar system*, 290
 JTIDS, *joint tactical information distribution system*, 284-299
 air-data backup, 297
 clock synchronization, 287 ff, 312
 community, 288 ff
 donor, 286
 errors, 297-299
 Kalman filter, 289, 293-294
 quality, 293
 relative navigation, 285
 RelGrid, 288
 signal-in-space, 286
 time reference, 289
 TOA only, 285
 with GPS, 286
 See also Multisensor navigation
 Julian date, 584
- Ka-band 101, 634
 Ke-band 101, 463
 Ku-band 101, 538, 545, 634, 671
 km, *kilometer*
 Kalman filter, 72-81, 559 ff
 cascaded, 94
 closed-loop, 79-81
 extended, 560
 GPS ground, 212
 GPS-inertial example, 83-91
 GPS orbit, 212
 GPS receiver, 228-229
 inertial alignment, 383-385
 in-flight calibration, 358, 593-594
 INS, 386
 JTIDS relnav, 285, 292 ff
 linearization, 78, 82
 magnetic compass, 444
 measurement model, 83, 560
 observability, 563
 Omega, 171
 open-loop, 77-79
 practical considerations, 91-93
 process model, 83, 88
 radar velocity, 527-529
 square-root form, 93
 stellar inertial, 61-64, 557 ff, 582, 590-593, 595
 U-D factorization, 93
 See also each navaid
- Kepler, J., 187, 225
 Keyboard, 698
 kHz, *kilohertz* = 103 Hz
 Kinematic GPS, 252, 629-630
 KLM airline, 597
 kn, *see* Knot
 Knot = one nautical mile per hour
 Korea, Loran coverage, 152
 Kronecker delta, 351
 kt, *see* Knot
 KVH Industries, Inc., 441
 Kwajalein Island, 208
- L1, GPS carrier frequency, 178
 L2, GPS carrier frequency, 178
 L-1011, 605
 LAAS, *local area augmentation system* 687
 Lambert conformal chart, 28
 Lag, *see* Delay; Latency
 Landing, 8-9, 600-605
 accidents, 598
 aircraft carrier, 630-636
 automatic, 605-608
 with DGPS, 628-630
 with Doppler-GPS, 498
 HUD usage, 637
 minimums, 8, 599 ff
 missed approach, 605
 navaids, 662
 nonprecision, 8, 600, 662
 optical aids, 633-634, 637
 procedure, 659-660
 radar altimeter, 497
 see to land, 599
 see to taxi, 599
 taxi, 681
 See also Airport; Approach; Category of landing;
 ILS; MLS
- Lane:
 ambiguity, 3, 162-164
 Decca, 171-172
 Omega, 155
- Laser:
 air data velocimeter, 418 ff
 inertial sensor, 326 ff
 radar, 637
- Latency:
 defined, 10-11
 data bus, 694
 Doppler maneuvers, 485
 during flare, 603
 during landing, 630
- Latitude:
 celestial, 556-557
 terrestrial, 23-24
- L-band, 101
 data link, 671
 DME, 133
 GPS, 198
 JTIDS, 285
 SSR, 665
 Tacan, 133
- LCD, *liquid crystal display*, 549
 LCP, *left-circularly polarized*, 333
 LDGPS, *local differential GPS*, 638
- Leakage:
 Doppler, 465
 radar altimeter, 493
- LEM (now LM), *lunar excursion module*, 450
 LEP, *linear error probable*, 253
 Leveling, inertial navigator, 382-384
 Levels, *see* Accelerometer
 Lever-arm correction:
 GPS, 278
 inertial system, 388
- LF, *low frequency*, 100, 106
 LHA, *local hour angle*
 LHA, LHD landing ships, 636
 LHCP, *left-hand circularly polarized*, 230
 Lidar, 418

- Light:
 aircraft carrier, 633–634
 background, *see* Atmosphere
 bars, 600
 speed of, 34, 101, 223
See also Airport
- Lightning:
 atmospheric, 105
 protection, 3, 19
See also EMI
- Linearization:
 GPS equations, 229
 of Kalman filter, 81–82
 of range measurement, 35
See also Filter
- Line of nodes, 185
- Line of position, *see* LOP
- Line-of-sight:
 GPS, 33–34, 181
 optical, 564
 radar, 523
 radio, 108–111
- Link budget, radio, 103–104
- Link-4, 634
- LLWAS, *low-level wind-shear alert system*, 673
- LNA, *low-noise amplifier*, 232, 493
- LO, *local oscillator*, 232, 247, 469, 493
- Lobe:
 antenna, 548, 665
 switching, 483
See also Antenna; Beam
- Lobing, simultaneous, 483
- Local controller, ATC, 655, 680
- Localizer:
 aircraft carrier, 635–636
 bends, 619
 description, 613–614
See also ILS
- Local level coordinates, 27, 365–373
- Lockheed, 245. *See also* C-130
- Longitude:
 defined, 234
 of satellite, 186
- Loop direction finder, 117
- LOP, *line of position*:
 celestial, 557
 described, 117, 264
 Decca, 171
 Loran, 112, 149
 Omega, 159
- Loran, 138–154
 accuracy, 143
 for approach, 652
 availability, 144
 blinking, 139, 145
 calibration, 146
 chain, 139
 with Chayka, 176
 differential, 146
 direct ranging, 145–146
 diurnal effects, 142
 false locks, 151
 geometry, 153
 hyperbolic, 13
 integrity, 145
 for landing, 618
 nonprecision approach, 8
 propagation error, 141
 receiver, 149–151
 repetition interval, 139
 seasonal effects, 142, 144
 signal-in-space, 139–140
 tracking, 151
 transmitter, 147–149
See also Ground waves; Sky waves; Multisensor Navigation
- LOS, *see* Line-of-sight
- Low observables, 532
- LP, *linearly polarized*, 230
- LPD *log-periodic dipole antenna*, 613
- LPH, landing ship, 636
- LPI, *low-probability of intercept*, 493
- LRM, *line replaceable module*, 700
- LRU, *line replaceable unit*, 691, 700
- LSO, *landing signal officer*, 633
- LTP, *local tangent plane*, 201
- m, *meter*
- m, *prefix milli* = 10^{-3}
- M, *prefix mega* = 106
- Mach number:
 calculation of, 400, 405
 effect on airspeed, 407
 effect on light, 578
 effect on pressure, 396–397
 effect on temperature, 398
- Magnetic compass:
 Compass Engine, 441
 deviation, 438–439
 in Doppler navigator, 489
 errors, 438–439, 442
 flux gate, 440–441
 hard iron, 438, 442
 needle, 439–440
 soft iron, 438, 443
 strapdown, 442, 447
 superconducting, 443, 447
- Magnetic field:
 declination, 437
 dip, 15, 437
 effect on gyroscopes, 341, 346
 effect on IMU, 363
 goniometer detector, 119
 mathematical model, 437 ff
 sensors, 440 ff
 variation defined, 437
 VOR reference, 176
- Magnetometer, *see* Magnetic compass
- Magnitude, star, 567–568, 570
- MAGR, *miniature airborne GPS receiver*, 243–245
- Magvar, 437
- Maintenance:
 air data, 412, 423–424
 avionic, 700
 dispatch, 703
 radar, 504
See also MTBF, MTTR
- mamp, *milliampere*
- Manchester coding, 692
- Manual navigation, *see* Human navigator
- Maneuver sensitivity, *see* Error
- Manometer, 404, 422–423
- MAP, *missed approach point* 654
- Map, *see* Chart; Display, map

- Map, real-beam, 501–509
 Map matching, *see* Terrain matching
 Marker beacon:
 description, 121–122, 618–619
 as final fix, 654
 landing, 599
 taxiway guidance, 605
 Markov process, 90, 297
 MASP, *Minimum Aviation System Performance Standard*, 251
 Master station:
 Decca, 171
 GPS control, 179
 Loran, 139
 Mathematical model, *see* Error; Simulation
 Matrix:
 antenna rotation, 527
 covariance, 75
 direction cosine, 27, 355, 366
 Kalman gain, 75
 measurement noise, 74
 observability, 563
 quaternion, 355–356
 rotation, 563
 McDonnell-Douglas Corporation, 4, 699
 See also Boeing; C-17; F-15; F-18; MD-x
 MCF, *Metroplex control facilities*, 679
 MCM, *multi-chip module*, 548
 MCOPS, *million complex operations per second*, 548
 MCS, *master control station*, 208
 MCU, *modular concept unit*, 235
 MD-11, 605, 695, 698
 MD-80, 605
 MDA, *minimum descent altitude*, 600
 MEA, *minimum en-route altitude*, 649, 657
 Measurement, *see each navaid*: Accelerometer;
 GPS; Gyroscope; Magnetic Compass; Sensor
 Mean time between failures, *see* MTBF
 Meatball, 633
 Mediterranean Sea, 152, 167
 Memory:
 DME, 131
 Loran, 149
 See also EPROM; RAM; ROM; Software
 Mercator, 28, 40
 Message:
 GLONASS navigation, 261–262
 GPS navigation, 218–226
 WAAS, 270–272
 Meteorology, *see* Weather
 Metering, ATC, 658, 678
 Metroplex, ATC, 679
 MF medium frequency, 100
 MFD, *multifunction display*, 695
 MF/DF, *medium-frequency direction finder*, 11
 MGR, *miniature GPS receiver*, 243
 MGRS, *military grid reference system*, 28, 302
 MHz, *megahertz* = 106 Hz
 Microbursts, 544, 599
 Microwave landing system, *see* MLS
 MIDS, 284, 311
 Military:
 airborne radar, 503
 aircraft carrier, 630–636
 aircraft types, 5–6
 air data, 408–409, 413–414
 airspace, 646
 avionics, 16
 celestial navigation, 594
 charts, 49–50
 cooling, 703
 Doppler radar, 450
 GPS, 198, 229 ff, 243–248
 helmet display, 697
 inertial navigators, 314, 390
 JTIDS, 284–299
 landing, 630–637
 MGRS, 28, 302
 mission planning, 17
 MLS, 622
 packaging, 702
 PLRS, 299–311
 radar, 503
 radar velocity error, 526
 sonobuoys, 6, 484
 standards, 19
 Tacan, 133–137
 tactical landing, 622, 638
 terrain avoidance, 529–533
 terrain matching, 534–536
 See also aircraft designations; Aircraft carrier;
 Helicopter;
 Radar, airborne
 Millibar, defined, 397
 Millimeter-wave, 636–637
 Millington (Loran), 146
 MIL-M-28787, 702
 MIL-STD-704 power, 700
 MIL-STD-1553 data bus:
 air data, 409
 description, 691–692
 Doppler radar, 490
 GPS, 235
 MIL-STD-1773, 693
 min, *minute*
 Minimum altitude:
 descent, 18, 600
 en-route, 649, 657
 landing, 652
 vectoring, 659
 warning, 674
 MIPS, *million instructions per second*, 548
 Mirror:
 laser gyro, 327
 telescope, 567
 Misalignment, *see* Alignment
 MIS, *metal insulator semiconductor*, 572
 Missed approach:
 aircraft carrier, 633
 described, 9, 599
 procedure, 654
 segment, 654
 See also Bolter
 Missile guidance, 8, 41
 Mission planning, 17, 21, 182
 Mixer, 470
 Mizar, 585
 MLS, *microwave landing system*, 620–628
 data transmission, 625–626
 in Europe, 687
 ICAO, 7
 mobile, 627
 redundancy, 627

- scanning, 623 ff
- signal-in-space, 621
- Shuttle landing, 636
- See also* DME/P
- MM, *middle marker* 618
- mm, *millimeter* (10–3 meter)
- MMIC, *microwave monolithic integrated circuits*, 493, 498
- MMLS, *mobile MLS*, 627
- MMO, *maximum operational Mach number*, 408
- MMWR, *millimeter-wave radar*, 636
- Mode A, 665–667
- Mode C, 409, 665–667
- Mode S:
 - described, 667, 670
 - display overlay, 50
 - TCAS coordination, 686
- Models, mathematical, *see* Filter; Simulation
- Modes, *see each* *navaid*
- Modulation:
 - air-ground communication, 670
 - depth of, Tacan, 134
 - difference in depth of, 609–610
 - Doppler radar, 466–469, 490
 - Doppler VOR, 126
 - fiber optic gyroscope, 337
 - fluxgate compass, 441
 - GLONASS, 259
 - GPS, 213
 - glide slope, 610–611, 614–616
 - JTIDS, 286
 - localizer, 609
 - marker beacon, 121
 - PLRS, 302
 - pseudonoise, 213
 - radio altimeter, 492, 498
 - of radio waves, 100
 - Tacan, 134–135
 - VOR, 123
 - wobbling, 495
- See also each radio navaid*
- Modulation index, 466, 468
- Monitor:
 - aircraft systems, 670
 - carrier landing, 635–636
 - data bus, 691–692
 - GPS, 179, 207–210
 - gyro, 325
 - ILS, 608
 - landing, 638
 - Loran transmitter, 149
 - Omega station, 156, 167
 - PLRS, 301
 - precision runway, 683
 - RAIM, 176, 264–265
 - WAAS, 269
- See also* BIT; Failure detection; Fault tolerance
- Monopulse, *see* Antenna
- Monte Carlo simulation, 376
- Moon, 210, 586
- MOPS, *Minimum Operational Performance Standards*, 235, 271
- MOS, *metal oxide semiconductor*, 572
- Motion compensation:
 - autofocus, 520
 - Doppler tuning, 515
 - range walk, 516
- SAR radar, 514, 518–522
- vertical reference, 433–434
- Morse code, 123, 133, 609, 618
- Moving target detection, 539–540
- mrad, *milliradian* = 10⁻³ radian
- MS, *master station*, PLRS, 300
- MS, *monitor station*, GPS, 208–210
- MSAS, *MTSAT satellite augmentation system*, 268
- MSAW, *minimum safe altitude warning*, 678
- MSBLS, *microwave scanning beam landing system*
- MSK, *minimum shift key*, 670
- MSL, *mean sea level*, 23, 38, 307, 644
- MSS, *mobile satellite services*, 259
- MTBF, *mean time between failures*:
 - avionics, 695, 700
 - inertial, 364
 - radar, 504
- MTBUR, *mean time between unconfirmed removals*, 700
- MTI, *moving target indication*, 541, 544
- MTSAT, *multi-functional transport satellite*, 268
- MTTR, *mean time to repair*, 202
- Multilateration, 42–43, 113, 283–284, 288
- Multimode radar, 538 ff
- Multipath effects:
 - altimeter, 495
 - description, 109–111
 - direction finder, 119
 - DME, 132
 - Doppler CW, 465
 - glide slope, 615
 - GPS, 228, 230–232, 250, 278
 - ILS bends, 619
 - ILS siting, 630
 - ionosphere, 107
 - PLRS, 309
 - Tacan siting, 138
 - VOR siting, 127
- Multisensor navigation:
 - air-data-inertial, 67–68, 97, 373–375
 - block diagram, 22
- Doppler-AHRS, 69–70
 - Doppler-inertial, 64–67, 451, 462, 477, 479
 - GPS-AHRS, 347, 389, 447
 - GPS-Doppler, 97, 451, 490, 498
 - GPS-GLONASS, 257–262, 267
 - GPS-inertial, 81–91, 629
 - GPS-JTIDS, 297
 - GPS-Loran, 69, 175
 - GPS-Loran-Doppler, 2069–70
 - JTIDS-air data, 297
 - JTIDS-inertial, 289
 - JTIDS multifunction, 311
 - Loran-Chayka, 176
 - Omega-inertial, 156
 - SAR-inertial, 511, 519
 - stellar-inertial, 61–64, 557 ff
 - stellar-inertial-Doppler, 68–69
 - theory of, 55 ff
 - VOR-inertial, 82
- NAS, *national airspace system*, US, 262
- NASA, *National Aeronautics and Space Administration*, US
 - air data, 418
 - Space Shuttle, 422

- NATO, *North American Treaty Organization*, 197, 198
- Nautical mile, defined, 25
- Navigator, human, 3, 19–20
- NAVSTAR, *see* GPS
- NC, *navigation controller*, 288
- NCO, *number-controlled oscillator*, 240
- ND, *navigation display*, 695
- NDB, *nondirectional beacon*, 12, 120–121, 662
- Network:
 - air traffic, 671
 - JTIDS, 284 ff
 - PLRS, 300 ff
- New York, 681
- NEXRAD, *Next-Generation Weather Radar*, 673
- NF, *noise figure*, 476
- Night, propagation, 117
- NIST, *National Institute of Science and Technology*, US, 575
- nm, *nanometer* = 10⁻⁹ meter
- nmi, *nautical mile* = 1852 meters,
- NNSS, *Navy navigation satellite system*, US, 178
- NOAA, *National Oceanic and Atmospheric Administration*, US, 152
- Node:
 - ascending, 186
 - com-nav, 283
 - descending, 186
 - line of, 185
- Noise:
 - abatement, 659–660
 - clock, 190
 - Doppler S/N, 476
 - Doppler spectrum, 460, 472–473
 - optical gyro, 331
 - radar jitter, 528
 - receiver, 102
 - scanning, 462–463
 - sensor, 70–71
 - velocity, 487
 - white, 83, 560*See also* Atmosphere: Correlation; Filter; Power spectral density; Spread-spectrum
- Noise figure, 102, 476
- Noise power, receiver, 102
- Northrop-Grumman Corp., 580, 582, 591
- NOTAM, *Notice to Airmen*, 661, 670, 680
- NovAtel Communications, Ltd., 235, 236, 237, 239
- NTR, *net time reference*, 286, 289
- Null, antenna, 110
- Null-reference glide slope, 614
- Nutation, astronomic, 587
- NWS, *National Weather Service*, US, 672, 680
- Nyquist rate, 548
- Oakland, 681
- OAT, *outside air temperature*, 398
- Observability:
 - Doppler radar, 65
 - Kalman filter, 91
 - radar, 529
 - stellar-inertial, 562–564
- Obstacle clearance, 648, 653
- Oceanic traffic:
 - Atlantic, 660
 - celestial navigation, 551
 - com-nav, 13, 660
- described, 660–661
- Pacific, 680–681
- regulations, 680–681
- OCXO, *oven-controlled crystal oscillator*, 233
- OEM, *original equipment manufacturer*
- Offset, parallel ATC, 663. *See also* Clock
- O'Hare International Airport, 275, 608
- OM, *outer marker beacon*, 602, 654
- Omega, 155–171
 - accuracy, 162–163
 - differential, 167
 - direct ranging, 164–165
 - hyperbolic, 162
 - lane ambiguity, 158, 163
 - over ocean, 650
 - propagation anomalies, 159–161
 - receiver, 169–171
 - RNAV, 649
 - signal-in-space, 157–159
 - sole means, 661
 - stations, 156–157
 - transmitters, 156, 168–169
 - with VLF, 167–169
- Omnidirectional range, *see* VOR
- Optical landing aid:
 - aircraft carrier, 633–634
 - enhanced vision, 636
 - FLIR, 636
 - focal plane array, 637
- Optical sensor, *see* Sensor
- OQPSK, *offset quaternary phase shift keying*, 670
- Orbit elements:
 - GLONASS, 257
 - GPS, 197–198
 - perturbations, 188–190
- Orbiter, *see* Space Shuttle
- Order wire, PLRS, 300
- Orthogonality, 560
- Oscillator:
 - DME crystal, 128
 - Doppler radar, 480
 - GPS, 232, 236
 - number-controlled, 240
 - optical, 327–336
 - OXCO, 233
 - radar altimeter, 493
 - TXCO, 233
 - VCO, 236
 - VFO, 524
 - VOR crystal, 123*See also* Clock
- OSI, *open system interconnection*, 671
- Outlier, 48
- P3V, 450
- P3V, 450
- Pacer Systems, Inc., 416
- Pacific Ocean:
 - Chayka, 175, 176
 - Inmarsat, 270
 - Loran, 152
 - Omega, 156
 - traffic control, 13, 680
- Packaging:
 - ARINC, 600, 701–702
 - inertial, 356–358, 362–363

- radar, 548
- SEM, 549, 702
- Packet, 671. *See also* MTBF; Weight; Power consumption
- Painting, radar 506
- PAR, *precision approach radar*:
 - land-based, 13, 652, 664
 - Russia, 13
 - shipborne 636
- Paradox:
 - mountain, 453–454
 - smooth Earth, 453
- Parallax, 555, 587
- Parallel approaches, 682–683
- Parallel processors, 540
- Parasitic element, Tacan, 134
- Partitioning, 18
- Pascal, B., 51
- Patch:
 - SAR, 509, 520
 - terrain-matching, 37
- PATCO, *pulse amplitude and timing controller*, 147
- Payload, GPS, 204–205
- PCD, *polar-cap disturbance*, 165
- PCDP, *pilot control display panel*, 301
- P-code, *precise code*:
 - GLONASS, 260
 - GPS, 216
- PDF, *probability density function*, 541
- PDOP, *position dilution of position*, 49, 201
- Pendulum, *see* Accelerometer
- Performance, *see* Error
- Perigee, 187
- Period of orbit, 187
- Perturbation:
 - orbital, 188 ff
 - state vector, 78*See also* Filter
- PFD, *primary flight display*, 695
- PGTR, *pulse group time reference*, 149
- Phase:
 - in-phase, 239–240, 247, 528
 - lock, 236
 - measurement, 32
 - quadrature, 239–240, 247, 528
- VOR, 126
- Phased-array, *see* Antenna
- Phases of flight, 7–10, 655–659
- Photoconductive, 572
- Photomultiplier, 573
- Photon, 572
- Photovoltaic, 572
- Pickoff:
 - accelerometer, 320
 - air-data probe, 417
 - gyroscope, 325, 344
 - inertial platform, 361
- Pick-up, *see* Detector; Pickoff
- Piezoelectric:
 - air-data, 402
 - cavity control, 331
 - mandrel, 337
 - torquer, 327
- PIGA, *pendulous integrating gyro accelerometer*, 323
- Pilot, *see* Display; Cockpit
- Pilotage, 504–505
- Pipeline processors, 540
- Pitot tube, 393 ff
- Pixel:
 - CCD, 572
 - defective, 592
 - telescope, 596
- PL, *see* Pseudolite
- Planar array, *see* Antenna
- Planck's constant, 572
- Planet, 586
- Plan position indicator, 506
- Plasma, ionosphere, 193
- Plates, *see* Charts
- Platform, inertial, 314, 348 ff
 - alignment, 382 ff
 - analytic, 314
 - 4-gimbal, 316, 363–364
 - gimballed, 361 ff
 - gimbal lock, 361
 - isolation, 356, 361
 - stellar, 552
 - strapdown, 356
 - temperature effect, 356, 363
 - vibration effect, 356, 362
- PLRS, *position location reporting system*, 299–311
 - accuracy, 309–310
 - altimetry, 305
 - capacity, 309
 - control network, 301
 - enhanced, 310
 - Kalman filter, 307
 - MGRS, 312
 - network management, 308–309
 - range measurement, 305
 - time offset measurement, 305
 - waveform, 302–304
- Pneumatic tubing, 396
- PMC, *power management control*, 493
- PN, *see* Pseudo-random noise
- P/N, *part number*
- Pointing:
 - precise, 594
 - to star, 556
- Polarization:
 - DME, 131
 - Doppler radar, 464
 - GPS linear, 206
 - laser gyro, 333, 340
 - radio waves, 104
 - VOR, 123, 125
- Polar regions:
 - air traffic control, 13
 - wander azimuth, 29
- POR, *Pacific Ocean region*, 270
- Port, static, 394, 422
- PORT structure, 301
- Positioning:
 - absolute, 114, 283
 - defined, 2
 - relative, 283
- Position Location Reporting System, *see* PLRS
- Position report, ATC, 660
- Position update, *see* Fix
- Positive control, 8, 12, 645
 - See also* Air traffic control
- Power, optical
 - sky, 568–572

- Power, optical (*cont'd*)
 star, 567-568
- Power, radiated:
 DME interrogator, 127
 DME transponder, 128
 Doppler radar, 490
 GLONASS, 258, 261
 GPS, 206
 Loran, 147
 marker beacon, 121
 Omega, 169
 pseudolite, 276
 radar altimeter, 491-493, 495, 498
 radar, phased array, 546
 radio navaid, 103
 VOR, 123
See also each navaid
- Power consumption:
 DO-160, 700-701
 gyroscope, 345
 inertial system, 317, 349
 MIL-STD-704, 700-701
 radar altimeter, 493, 495, 498
- Power spectral density, 219, 479
- PPC, *predicted propagation correction*, 159
- PPI, *plan position indicator*, 506
- PPLI, *precise position location and identification*, 284-285
- PPM, *pulse-position modulation*, 665, 670
- PPS, *precise positioning service*:
 accuracy of, 245
 description, 198
 error budget, 253
- PPS-SM, *PPS Security Module*, 248
- Preamble:
 GPS, 220
 JTIDS, 285
 PLS, 302
 WAAS, 271
See also Data bus
- Preamplifier, *see* Amplifier
- Precession:
 astronomic, 584, 586-589
 gyroscopic, 343
 vertical gyro, 432
- Precipitation, *see* Rain
- Precise positioning service, *see* PPS
- Pressure:
 dynamic, 396
 helicopter dynamic, 414
 impact, 396
 pitot, 396
 static, 394
 total, 396
- Pressure altitude, 404
- Pressure-pattern navigation, 12, 41, 661
- PRF, *pulse repetition frequency*, 493, 498
- PR1, *pulse repetition interval*, 540
- Principal axes, 45
- PRM, *precision runway monitor*, 683
- PRN, *Pseudo-random noise*, *see* Spread-spectrum
- Probability:
 CEP, 45
 Gaussian, 46
 GPS codes, 214-216
 integrals, 46
 landing accident, 597
 SEP, 48
 three dimensional, 48
See also MTBF; Safety of flight
- Probe, air data:
 angle of attack, 399-400
 intrusive, 394
 flush, 394, 422
 omnidirectional, 415
 pitot-static, 394-396
 recovery factor, 399
 rotating, 414-416
 swivel, 417
- Profile, *see* Terrain matching
- Program pins, 409
- Programming, *see* Software
- Prohibited area, 646
- Projections, map, *see* Charts
- PROM, *programmable ROM*:
 ARINC bus, 694
 data storage, 51
 personality, 694
- Propagation, radio:
 description, 99 ff
 diurnal, 142, 160
 JTIDS, 298
 Loran over water, 146
 Omega, 160-161
 seasonal, 142, 160
- Proportional navigation, 41
- Protocol, communication, 671
- Pseudolite:
 coverage, 202
 described, 13, 275-278
 landing, 630
 WAAS, 275
- Pseudo-random noise, *see* Spread-spectrum
- Pseudorange:
 calculation of, 34-35, 89
 definition, 181
 GPS measurement, 226-227
 radio navigation, 114
- Psi-angle, 62, 558
- PTH, *path*, 696
- PTTI, *precise time and time interval*, 139
- Pulse:
 compression, 545
 group, Loran, 139
 Tacan, north, 136
- PVU, *precision velocity update*, 453, 504
- Q-ball, 421
- Quadrature, 234, 528
- Quality of navigation:
 GPS health, 221-222
 JTIDS, 289
 MLS confidence, 626
 PDOP, 202
See also Errors
- QPSK, *quadrature phase-shift keying*, 278, 670-671
- Quaternions:
 strap-down inertial, 352-353, 355
 JTIDS, 293
- RA *resolution advisory*, 686
- Rad, *radian*
- Radar:
 equation, 472-477

- history, 503
- millimeter wave, 637
- signal processing, 539–540
- software, 539, 547–548
- Radar, airborne:
 - fluctuations, 513
 - mapping, 503 ff
 - military target, 5
 - multimode, 29, 451, 457, 503, 524, 538 ff
 - pencil beam, 533, 538
 - reliability, 504
 - resolution, 505, 508
 - search, 664
 - sensitivity, 507
 - shadowing, 508
 - terrain avoidance, 504, 529 ff
 - terrain-following, 529 ff
 - warning time, 533
 - weather, 540–545
 - See also* ACRS; Altimeter, radar; Doppler radar; PAR; SAR; ??????????Weather radar
- Radar, traffic control:
 - airport surveillance, 652
 - approach vectors, 600
 - ASR, 679
 - carrier landing, 634–635
 - display, 658
 - ground-controlled approach, 636, 664
 - height-finding, 664
 - primary, 664
 - procedures, 662
 - secondary surveillance, 664–667, 687
 - Tracon, 679
 - transponder, 665
 - See also* Separation
- Radiance, sky, 569
- Radiation:
 - hardening, 206
 - natural, 10
- Radio altimeter, *see* Altimeter; Radar
- Radio-frequency interference, *see* EMI
- Radio-magnetic compass, 426
- Radio navigation:
 - history, 11–14, 100
 - radiated power, 103
 - See also each navaid*
- Radionavigation Plan, US, 705
- Radio Technical Commission for Aeronautics, *see* RTCA
- Radio Technical Commission for Maritime Services, *see* RTCM
- Radius of curvature:
 - Gaussian, 25
 - meridian, 25, 370
 - prime, 25, 370
- Radome, 4–5, 125, 230, 465–466, 480, 626
- Rails, cooling, 703
- RAIM, *receiver autonomous integrity monitoring*, 264–268
- Rain:
 - attenuation in, 109
 - detection by radar, 542
 - effect on air-data, 399
 - effect on GPS, 195
 - effect on radar, 476, 533–534
 - effect on weather radar, 540, 542–543
 - IR absorption, 637
 - landing, 599
- RAM, *random-access memory*
- Random route, *see* RNAV
- Random walk, *see* Noise
- Range:
 - bin, 515, 519 ff
 - cell, 534 ff
 - calculation of line-of-sight, 33–35
 - clock error, 35
 - dynamic, 507
 - in ECEF, 233
 - iterative calculation, 33–35
 - Millington's method, 146
 - one-way, 35–36
 - range-to-go, 21, 38–40
 - samples, 506
 - slant, 33, 550
 - trace, 506
 - two-way, 32
 - walk, radar, 516–517
- Ranging:
 - DME, 81–82
 - GPS, 229
 - with JTIDS, 288
 - line of sight, 112, 181
 - with PLRS, 305
 - pseudorange, 34, 181
 - WAAS, 273
 - while search, 538
 - See also* Multilateration
- Ranging, direct:
 - Loran, 145–146
 - Omega, 164–165
- Range-rate calculation, 183–184
- RAPCON, *radar approach control center*, 655, 679
- Rayleigh scattering, 421
- Rb, *Rubidium*, 204
- RBGM, *real beam ground map*, 504–509, 538
- RCAG, *remote communication air-ground site*, 677
- RCP, *right circularly polarized*, 333
- RCS, *radar cross section*, 542
- Reasonability test:
 - JTIDS relnav, 294
 - Kalman filter, 92
- Reasonableness, *see* Reasonability test
- Rebalance loop:
 - accelerometer, 320–322
 - mechanical gyroscope, 343, 345
 - optical gyroscope, 339
- Receiver, *see each radio navaid*
- Receiver autonomous integrity monitoring, *see* RAIM
- Reconnaissance, 6
- Recovery:
 - factor, probe, 398
 - time, DME, 70–72, 130
- Recursive filter, *see* Kalman filter
- Redundancy, *see* Fault tolerance
- Reference:
 - pulse, Tacan, 134
 - points, radar, 505
 - station, GPS, 248
- Reflection, *see* Mirror; Multipath
- Reflectivity:
 - clouds, 542
 - dust, 544

- Reflectivity (*cont'd*)
 radar, 507–508
 rain, 542, 545
 See also Mirror; Multipath
- Refraction, *see* Atmosphere; Ionosphere;
 Troposphere
- Refractive index, 35, 193
- Refueling, 6
- Relative navigation, 283
- Relativity, 227
- RelGrid, 288
- Reliability:
 air data, 412
 inertial navigator, 364
 Loran, 144
 radar, 504
 of software, 18
 temperature effect, 703
 See also Availability; MTBF
- RelNav, 284
- Remotely piloted vehicles, 6
- Repair, *see* Maintenance
- Repeatability, Loran 144–145
- Repetition rate:
 DME, 127
 Loran, 132, 140
 radar altimeter, 493, 498
 weather radar, 544
- Reporting, ATC, 660
- Required navigation performance, 235, 662
- Rescue, *see* Search and rescue
- Residuals, GPS, 229
 See also Errors
- Resolution:
 A/D converter, 402
 advisory, 686
 optical, 565, 572
 radar, 511 ff
- Resolvers:
 gimbal, 317
 star tracker, 577, 579
- Resonance:
 accelerometer, 320
 optical gyroscope, 326
 tuned rotor, 344–345
 vertical gyroscope, 433
 See also Tuning
- Restoring loop, *see* Servo
- Restricted area, 646
- RF, *radio frequency*
- RF, *remote facility*, 208
- RFI, *radio frequency interference*, *see* EMI
- RH, *relative humidity*, 195
- RHCP, *right-hand circularly polarized*, 230
- Rho-rho fix, 113
 See also Multilateration
- Rho-theta fix, 113
- Rhumb line, 40
- Right ascension, 200, 553
- Risk, collision, 10, 606
- RLG, *ring-laser gyro*, 326 ff
- RMS, *root mean square*, 46
- RNAV, *random navigation*:
 computation, 42–44
 described, 7, 649
 GNSS, 687
 MLS, 626
 oceanic, 661
 separation, 663
- RNP *see* Required navigation performance
- Rockwell, dust jacket photo
- Rollout, on runway, 599, 604–605
- ROM, *read-only memory*, 21, 51
- Rosemount, Inc., 395
- Rotation:
 axis of, 352
 of Earth, *see* Earth
 Euler angles, 349
 on takeoff, 7
 See also Direction cosines; Quaternions
- Round-off, 92
- RPV, *remotely piloted vehicle*, *see* UAV
- RS, *radio set*, 300
- RSS, *root sum square*
- RS-232, serial data bus, 409
- RSBN, CIS navigation aid, 13
- RT, radio transmitter, 174
- RTCA, formerly *Radio Technical Commission for Aeronautics*:
 altimetry, 727
 air traffic management, 738
 avionics standards, 19, 705–739
 DGPS landing, 251, 252, 713
 Doppler radar, 730
 GPS, 235, 713
 ILS specifications, 608
 landing, 735
 marker beacon, 619
 radio nav aids, 710
 software, 51
 WAAS, 718–719
- RTCM, *Radio Technical Commission for Maritime Services*, 250, 252, 715
- RTR, *remote transmitter/receiver*, 679
- RTT, *round-trip timing*, 286–287
- RTTI, *round-trip timing interrogation*, 286
- RTTR, *round-trip timing reply*, 286
- Rubidium clock, 204
- Runge-Kutta, 261
- Runway:
 active, 656
 aircraft carrier, 630–631
 ATM, 660
 capacity model, 690
 environment, 651
 ILS installation, 619
 incursion, 604–605
 monitor, 683
 surveillance, 600
 See also Airport
- Runway dimensions:
 aircraft carrier, 630
 fixed, 600
- Russia, *see* CIS
- RVR, *runway visual range*, 599
- S3A, 450
- SA, *selective availability*, GPS 198, 235
- Safety-critical:
 air data, 399
 air speed 413
 avionics, 16, 703
 DGPS, 248–249
 engine controls, 16

- flight control, 599, 606
- partitioning, 18
- terrain following radar, 536–538
- software, 51
- traffic control, 678
- WAAS, 268
- See also* Fault tolerance
- Sagnac effect, 326
- Sampling:
 - aliasing, 247
 - Kalman filter, 94
 - See also* Filter
- SAR, *synthetic aperture radar*, 511–522
 - antenna scan, 509–511
 - array time, 512
 - autofocus, 519
 - beam sharpening, 504 ff
 - focussed, 516–518
 - future, 549
 - image formation, 508, 512 ff
 - patch, 509, 520
 - polar format, 519
 - real beam, 504 ff, 518
 - rectangular format, 518
 - scalloping, 509
 - strip maps, 516
 - terrain features, 508
 - unfocussed, 514–516, 518
 - utilization, 505–509
- SARP, *Standard and Recommended Practice*, 608
- SARSAT, *search-and-rescue satellite-aided tracking*, 16
- Satellite navigation history, 178. *See also* GLONASS; GPS
- Saudi Arabia, 176
- SAW, *surface acoustic wave*, 236
- S-band, 2–4 Ghz
- SBAS, *satellite-based augmentation system*, 268
- SBO, ILS *sidebands-only signal*, 609
- Scale factor:
 - accelerometer, 323–324
 - gyro, 341
- Scalloping, radar, 509
- Scan, radar, 506, 532, 538
- Scattering, optical, 330, 335
- Scattering, radar:
 - Doppler noise, 462–463
 - sea, 481–485
 - terrain, 474–475
- Schiphol Airport, 597
- Schuler frequency:
 - damping, 91
 - defined, 373, 377
 - illustration, 59, 567
- Scintillation:
 - radio, 195
 - SAR, 508
 - star, 578
 - TF/TA radar, 535
- Scorsby table, 365
- Scramjet, 421
- Sculling, 359
- SDF, *single-degree-of-freedom*,
- SDLCL, *synchronous data link control*, 210, 212
- Sea:
 - bias, radar, 481
 - state, 475
 - water, Loran, 143
 - water, Omega, 160
- SEADS, *Shuttle Entry Air-Data System*, 422
- Sea level:
 - atmosphere, 397, 644
 - map, 23, 38
 - refraction, 578
- Search:
 - DME, 67, 130
 - Loran, 149
 - radar, 511
- Search and rescue, 16, 119, 605, 642, 657
- sec, *second of time*
- Secondary phase factor, 143
- Secondary surveillance radar, 665
- Sector, ATC, 656
 - controller, 677
 - departure, 657
 - terminal, 679
- Segment:
 - final approach, 654
 - GPS, 207 ff
 - initial approach, 652–653
 - intermediate approach, 653–654
 - missed approach, 654
- Selective availability, *see* SA
- Self-test, *see* BIT
- SEM, *standard electronic module*, 702
- SEM-E, *SEM size E*, 549, 702
- Sensitivity, receiver, 102
- Sensitivity time control, 507
- Sensor:
 - air data, 393 ff, 400
 - airspeed, 396–397
 - acoustic, 6, 348, 417
 - angle of attack, 399–400
 - CCD, 553, 572–573, 596
 - electrolytic level, 429
 - inertial, 317–348
 - magnetic, 437–443
 - military target, 5
 - navigation, 21
 - photo, 327–328
 - pressure, 394–397
 - quantum of, 572
 - star, 572–574
 - temperature, 598–599
 - See also* Accelerometer; Dead-reckoning; FLIR; Gyroscopes; Star
- Sensor Systems, Inc., 235, 238
- SEP *sphere of equal probability*, also called *spherical error probable*, 48, 207
- Separation of aircraft:
 - alert, 678–679
 - approach, 659, 682
 - in controlled airspace, 645
 - longitudinal, 650
 - metering, 678
 - oceanic tracks, 660–661
 - procedural 12, 649
 - radar, 651
 - standards, 649–651, 663–664
 - TCAS, 685
 - vertical, 651
 - visual, 651
 - wake turbulence, 659

- Separation of aircraft (it cont'd)
See also Airspace; Air traffic management;
 Collision Avoidance
- Servo:
 accelerometer restoring, 320
 air data, 393
 gimbal drive, 361–363
 goniometer, 117
 Tacan antenna, 136
- Sextant, 551
- SF, *secondary phase factor*, 143
- Shadowing, 508
- Shear, *see* Wind shear
- SHF, *super-high frequency*, 100
- Shimmer, star, 578
- Shock and vibration, *see* Vibration
- Shock wave, *see* Supersonic
- Shupe Effect, 340
- SID, *standard instrument departure*, 16, 49, 655
- Sidebands, 466, 609
- Side lobe:
 Doppler radar, 461
 suppression, 665
- Side-looking radar, *see* SAR
- Sidereal day, 200, 554
- Sideslip, 399–400, 603–604
- Signal-in-space:
 GPS, 213–218
 Loran, 140–141
 Omega, 157–159
 Tacan, 135
 VOR, 123
See also each navaid
- Signal processing, *see each navaid*; Filter; Kalman filter
- Signal-to-leakage ratio, 465
- Signal-to-noise ratio, 103, 241, 472, 476, 533, 573
- Silicon sensors:
 air data, 402
 inertial, 321, 347
- Simplex data bus, 691
- Simulation:
 baro-inertial, 373–375
 inertial, 376 ff
 landing, 604
 Monte Carlo, 376
 stellar-inertial, 561–562
 training, 52
See also each navaid; Error; Kalman filter;
 Multisensor navigation
- SINS, *ship's inertial navigation system*, 314
- Sirius, 555
- SITAN, 38
- Siting errors:
 glide slope, 616–617
 Tacan, 136
 VOR, 127
- SKE, *stationkeeping equipment*
- Skip distance, 107
- Sky background, 568–572
- Sky wave, Loran:
 propagation, 106–108
 pulse contamination, 140
- Slave station:
 Decca, 171
 Loran, 139
- Slip, landing, 604, 607
- Slip rings, 363
- Slot, *see* Time slot
- SM, *security module*, 248
- Smart probes, 492
- Smart skin, 549
- smi, *statute miles* = 5280 feet
- Smoothing, *see* Filter; Delay
- S/N, *see* Signal-to-noise ratio
- Snell's Law, 577
- Snow, *see* Rain
- SNR, *see* Signal-to-noise ratio
- Soft iron, 438
- Software:
 contents of, 21, 411, 507, 539
 cost, 52
 development sequence, 51–52
 independent verification, 251–252
 loading, 21, 52
 radar, 539–540, 547
See also each navaid; Filter; Kalman filter
- Solar:
 activity, 194
 array, 204
 illumination, 162, 571
- Sole means of navigation, 11, 661, 687
- Sonobuoy, 6, 484
- Sound, speed of, 397. *See also* Acoustic
- South America, 11, 208
- Soviet Union, *see* CIS
- Space segment, GPS, 179
- Space Shuttle:
 air data, 393, 422
 landing, 636
- Space wave, 141
- Spacing, *see* Separation
- Specification, *see* ARINC; Eurocae; ICAO;
 RTCA
- Specific heat, air, 397
- Spectrum:
 Doppler radar, 460 ff
 GLONASS, 260
 GPS, 216–217
 multi-mode radar, 523, 525
See also Frequency bands; Spread spectrum
- Spectral density, *see* Power spectral density
- Speech:
 recognition, 699
 synthesis, 699
- Speed
 landing, 600, 603, 631
 of light, 101, 223
 of sound, 397
See also Airspeed
- Sperry Corp. *see* Honeywell
- Spherical harmonics:
 gravity model, 188
 magnetic model, 437
- Spherical triangle, 40
- SPI, *special identification pulse*, 665
- SPN-35, 636
- SPN-41, 42, 46, 631–636
- Spread-spectrum:
 GPS, 198, 234
 JTIDS, 286
 PLRS, 302
- SPS, *standard positioning service*:
 accuracy of, 198, 253 ff

- described, 198
- landing, 629–630
- SR-71, 551
- SRC, *sensitivity range control*, 492
- SS, *space segment*, GPS, 179
- SSR, *secondary surveillance radar*, 665
- Stable element, *see* Platform; Inertial
- Stable platform, *see* Platform; Inertial
- Stability, filter, 92
- Stabilization:
 - celestial, 577
 - Doppler radar, 457–460, 485
 - heading references, 426 ff
 - inertial, 314, 361–362
 - Tacan transmitter, 134
- Stall margin, 603
- STANAG 3910, 693
- Standard:
 - arrival, 655
 - atmosphere, 397
 - departure, 655
 - deviation, 46
 - positioning service, *see* SPS
- Standards,
 - avionic, 19
 - separation, 663–664
 - See also* ARINC; DoD; Eurocae; ICAO; IEEE; RTCA
- Standard terminal arrival route, *see* STAR
- STAR, *standard terminal arrival route*, 16, 655
- Star:
 - catalog, 556, 583–590
 - calculation, 590–593
 - detector, 571–573
 - double, 585
 - geometry, 553–557
 - irradiance, table, 570
 - magnitude, 567–569, 583
 - measurement, 552
 - pointing error, 576–578
 - position calculation, 586–590
 - quantum efficiency, 574
 - signal power, 567–568
 - spectral characteristics, 567–568
 - variable, 584–585
- Star tracker:
 - detached, 577
 - gimballed, 576
 - strapdown, 563, 577, 581–583
 - See also* Celestial navigation; Telescope
- State vector:
 - defined, 1, 73
 - dimensions, 90
 - GPS, 91
 - inertial, 90
 - JTIDS, 289
 - stellar-inertial, 560
 - See also* Filter; Kalman filter
- Static defect, 394
- Static source, 413
- Statistics:
 - distribution of errors, 45
 - Gaussian, 46
 - stationary, 44
 - variance, 46
 - See also* Covariance; Noise
- STC, *sensitivity time control*, 507
- Steering:
 - airway, 40–42
 - carrier landing, 633
 - course-line, 38–42
 - direct, 40–41
 - great circle, 40
 - guidance, 2
 - inertial, 373
- Stellar-inertial navigation, 68, 557 ff
- STOL, *short takeoff and landing*, 6. *See also* VTOL
- Strapdown:
 - magnetometer, 440–442
 - radar antenna, 459
 - stellar sensor, 64, 581–583, 594
- Strapdown INS, 348 ff
 - mechanization, 348–353
 - packaging, 356–359
 - performance, 359–361
 - quaternions, 352–354
 - role of gyroscope, 325
- Strouhal number, 416, 553
- SUA, *special-use airspace*, 688
- Subframe, GPS, 220
- Sunspots, 106
- Supersonic:
 - Mach calculation, 405
 - optical shock wave, 578
 - radar reflection, 465
 - See also* Hypersonic
- Supplemental navigation, 235, 266, 661
- Surveillance:
 - automatic dependent, 1, 667–669
 - radar, 664–667, 683
 - on runway, 605
- Surveyor, 450
- Swath, range, 507, 519, 538
- Swerling, P., 536
- Swinging:
 - compass, 439, 443–444
 - with Doppler radar, 490
- Switch, land-sea, 483
- Swiveling probe, 417–418
- Synchro:
 - air data computer, 400
 - direction finder, 445
 - Doppler radar, 459
 - magnetic compass, 441
- Synchronization:
 - bit, 242
 - frame, 242
 - GPS codes, 216
 - GPS navigation data, 218
 - JTIDS, 286–287
 - Loran, 147
 - of measurements, 92
 - Omega, 158
 - PLRS, 300
 - VLF, 167
 - See also* Time measurement
- Synchronous satellite, 268
- Synthesizer, GPS, 239
- Synthetic aperture radar, *see* SAR
- Synthetic array, *see* SAR
- TA, *traffic advisory*, 658, 686
- TA, *terrain avoidance*, 504

- TACAN, *tactical air navigation*:
 aircraft carrier, 134, 633
 approach fix, 600
 military usage, 5
 receiver, 135-137
 signal-in-space, 133
 transmitter, 133-135
- Takeoff, 7
 rapid, 593
- Tanker, 5
- Target:
 chart, 49-50, 378
 military, 5
 radar, 534
- Taxi, *see* Landing
- Taylor series, 520
- TCAS, *traffic alert and collision avoidance system*:
 description, 684-686, 689
 display overlay, 50
 speech cues, 699
- TCXO, *temperature compensated crystal oscillator*, 233
- TD, *dynamical time*, 576
- TD, *time difference*, 139
- TDF, *two-degrees-of-freedom*, 343-345
- TDMA, *time-division multiple access*:
 JTIDS, 287
 PLRS, 303
- TDOP, *time dilution of position*, 49, 201
- TDWR, *terminal Doppler weather radar*, 673
- TEC, *total electron content*, 194
- Telemetry, GPS, 212, 218-221
- Telescope:
 design, 96, 564-566
 gimballed, 579-580
 optic, 514-516
 stabilized, 563, 578
 strapdown, 552, 563
 pointing commands, 557, 576
- Temperature:
 accelerometer error, 323
 antenna error, 480
 avionics bays, 703
 effect on reliability, 703
 free stream, 398
 lapse rate, 644
 optical effects, 578
 outside air, 398
 stagnation, 398
 star, 568
 total, 398
- Temperature-compensation:
 air data, 399, 402
 beam direction, 480
 gimballed platform, 363
 inertial instruments, 321, 331, 340, 346, 381, 429
 optical gyroscope, 340
 oscillator, 232-233
- Template, voice, 699
- TERCOM, *Terrain Contour Mapping*, 38
- Terminal:
 control area, 645
 instrument procedure, 657
See also Airspace
- TERPROM, 38
- TERPS, *terminal instrument procedures*, 652, 736
- Terrain:
 approach, 615-618
 avoidance radar, 529 ff
 digital maps, 37-38
 errors, radar, 474, 481
 following radar, 529 ff
 glide slope bends, 619
 land-water boundary, 506
 matching, 37
 measurement, radar, 38, 534-536
 patch, 37-38, 509, 520
 profiling, 38, 530
 radar image, 505, 508
 radar reflection, 67, 453-454, 474, 508-509
 scattering, radar, 474 ff
See also Glide slope; Radar, Airborne
- Testing:
 accelerometer, 324
 air data, 422
 Doppler radar, 489
 flight, 299, 311, 379, 394, 409, 413, 418, 422-423, 489 7/ 8/10
 mechanical gyroscope, 347
 optical gyroscope, 342
See also Compensation; Calibration; Swinging
- Textron Defense Systems, 627
- TF, *see* Terrain following
- TF/TA, *terrain following/terrain avoidance*
- TFM, *traffic-flow management*, 542
- Theodolite, 381, 439
- Threshold, optical, 574. *See also* Landing
- Throttle management, 15
 carrier landing, 635
 Category II, III, 599
- TID, *travelling ionospheric disturbance*, 194
- Tidal effect:
 landing altimeter, 607
 radar, 484
- Timing, 197
- Time constant, *see* Delay
- Time definition:
 dynamic, 576
 universal, 207, 226
- Time-difference, Loran, 139
- Time measurement:
 absolute, 13, 226
 Allan variance, 190-192
 atomic, 204
 celestial navigator, 551, 575-576
 difference, 32, 139
 from GPS, 255
 history, 13
 from JTIDS, 289
 WWV, 575
See also Clock
- Time of arrival:
 ComNav, 283
 GPS, 184
 JTIDS, 284 ff
 Loran, 36, 145-146
 PLRS, 299 ff
 Omega, 36
- Time slot:
 DME, 130
 JTIDS, 284 ff
 Loran, 149
 PLRS, 304

- Time to closest approach, 685
 Time Reference Scanning Beam, 621
 TLM, *telemetry word*, 218 ff
 TMU, *traffic management unit*, 677–678
 TOA, *see* Time of arrival
 TOPCO, *transmitter operational control*, 147
 Torquer:
 accelerometer, 319
 directional gyro, 445
 gyro, 325, 343, 345, 431, 444, 583
 mechanization, 371
 platform, 314
 Touchdown:
 aircraft carrier, 631
 tolerances, 604
 wheel path, 602
 See also Landing
 TOW, *time of week*, 204
 Tower:
 air traffic control, 655, 679–680
 as radar target, 533–535
 T/R, *transmit/receive*, 546
 TR-1, 245
 TRACAB, *terminal radar approach colocated with tower cab*, 679
 TRACE, *track review and correction estimation*, 307
 Trace, range, 506
 Track:
 angle, illustration, 30
 oceanic, 660
 processing, 678
 terrain matching, 37
 toward target, 40
 Tracker, electronic:
 altitude, 493
 carrier phase, 242, 248
 DME, 131
 frequency, 469–472
 GPS code, 241–242, 248
 leading edge, 492
 Loran, 151
 mapping radar, 511
 sine-cosine, 471
 while scan, 538
 TRACON, *terminal radar approach control center*, 655, 679
 Traffic, *see* Air space; Air traffic management
 Training:
 CBT, 20
 maintenance, 701
 radar operator, 506
 simulator, 52
 Transducer, air data, 400. *See also* Sensor
 Transfer alignment, 386–388
 Transit, 178
 Transmissometer, 599
 Transmitter, *see each radio navaid*
 Transponder, ATC, 657, 658, 665–667. *See also*
 Beacon; Interrogator
 Transverse pole, 28–29
 Trident aircraft, 605
 Trilateration, *see* Multilateration
 Troposphere:
 delay, 249, 272
 refraction, 195–197, 227–228
 Truncation, 92
 Tsikada, 178
 TSO, *technical standard order*, 235
 TT&C, *telemetry, tracking and control*, 270
 Tubes, air data, 396, 412
 Tuning:
 gyrocompass, 436
 gyro suspension, 344
 Kalman filter, 92
 optical cavity, 331
 See also Filter; Radio nav aids
 Turbulence:
 clear air, 418, 543
 shimmer, 578
 wake, 659
 Turn and bank indicator, 11, 400
 TWT, *travelling wave tube*, 546
 TXCO, *temperature-controlled crystal oscillator*, 233
 U-2, 245, 551
 UAV, *unmanned airborne vehicle*:
 Doppler radar, 450, 490
 mission, 6
 navigation of, 311
 radar altimeter 497
 vehicle, 5
 UDRE, *user differential range error*, 250
 UERE, *user equivalent range error*, 253
 UHF, *ultra-high frequency*, 100
 United Kingdom, 417, 437, 598, 605
 United States:
 Air Force, 197, 208, 245, 530, 692, 725, 735
 Army, 413, 474, 480, 726
 Naval Air Engineering Center, 632, 633
 Naval Research Laboratory, 637
 Navy, 178, 197, 245, 633, 635
 See also FAA; Military; NWS; USCG
 Unmanned airborne vehicles, *see* UAV
 Update, *see* Fix
 Uplink, *see* Data link
 Upload, GPS, 207
 URA, *user range accuracy*, 221
 URE, *user range error*, 207
 URO, *user readout*, 301
 USCG, *United States Coast Guard*, 119, 145, 153, 175
 USNO, *US Naval Observatory*, 207–208, 262
 USSR, Union of Soviet Socialist Republics, *see* CIS
 UT, *universal time*, 576
 UTC, *universal time coordinated*:
 celestial, 575–576
 GLONASS, 262
 GPS, 207, 218, 226, 255
 Loran, 139, 155
 UTM, *Universal Transverse Mercator*, 28
 Validity test, *see* Reasonability test
 Vane:
 angle of attack, 399
 angle of sideslip, 399
 pivoted, 395
 swiveling, 417
 Variance, 46. *See also* Allan variance; Statistics
 Variation, magnetic, 437
 VCO, *voltage-controlled oscillator*, 236
 VDI, *vertical deviation indicator*, 613
 VDOP, *vertical dilution of position*, GPS, 201, 253

- Vector:
 air traffic, 655, 659
 celestial error, 558
 gravity, 23
 state, 1
- Velocity:
 dead reckoned, 29
 Doppler-measured, 449 ff
 GPS-measured, 255
 group, 193–194
 illustrated, 30
 inertially-measured, 313 ff
 JTIDS, 285
 phase, 193
 PVU, 522
 SAR, 518–522
 touchdown dispersion, 607
- Vertical:
 apparent, 23
 astronomical, 23
 defined, 23
 deflection of the, 25
 gyro, 429–436
 separation, 65
 true, 23
- Vertical gyroscope, *see* Gyroscope; Vertical
 Vertical position, *see* Altitude
- VFO, *variable frequency oscillator*, 524–525
- VFR, *visual flight rules*:
 clearance, 657
 in controlled airspace, 645
 described, 643 ff
 transponder code, 665
- VHF, *very high frequency*, 100
- VHF, omnidirectional range, *see* VOR
- Vibrating beam accelerometer, 322
- Vibrating diaphragm sensor, 402
- Vibrating string accelerometer, 322
- Vibration:
 accelerometer, 322
 directional gyro, 446
 effect on alignment, 384 ff
 effect on oscillator, 233
 gimballed platform, 362
 gunfire, 6–7
 gyroscope, 331–333, 340
 strapdown system, 359
See also Acceleration
- Vibropendulous error, 320
- Victor airway, 646
- Video, radar, 512
- Visibility, 597, 645–646, 657. *See also* Ceiling
- Visual charted procedures, 660
- Visual flight rules, 643–644
- Visual separation, *see* Separation
- VLF, *very low frequency*, 100
- VLF, Omega, 167–168
- VMC, *visual meteorological conditions*,
 651 ff
- VMO, *maximum operational velocity*, 408
- Von Karman, 415
- VOR, *VHF omnidirectional range*:
 approach fix, 600
 block diagram, 125
 Doppler, 126–127
 high altitude, 646
 low altitude, 646
 radome, 125
 receiver, 125–127
 signals-in-space, 122–123
 terminal, 646
 transmitter, 122–125
- VOR/DME:
 airways, 42–44
 approach, 652
 description, 122–126
 Doppler, 646
 RNAV, 646
 RNP, 663
- VORTAC *VOR-Tacan*:
 ATM, 646
 description, 138
 steering, 41–44
- Vortex transducer, 415–416
- VSI *vertical situation display*, 427
- VTOL, *vertical takeoff and landing*, 636. *See also*
 STOL
- w, *watt* = joule/second
- WAAS, *wide-area augmentation system*:
 ATM, 663, 687
 description, 268–274
 en-route, 15
 landing, 252
- WADGPS, *wide-area DGPS*, 252, 268
- Wake turbulence:
 aircraft, 659
 ship, 631
- Wander angle, *see* Azimuth; Wander
 Wander azimuth, *see* Azimuth; Wander
 Warm-up, INS, 381
- Water:
 scattering, 475
 sea bias, 481
 sea current, 484
 sea state, 475
 tidal offset, 484
- Wave, electromagnetic:
 guide, 161
 line-of-sight, 108–111
 Loran space, 141
 number, 159–160
See also Ground wave; Sky wave; Space wave
- Wave-off, *see* Bolter
- Watts Antenna Company, 618
- Waypoint:
 description, 16, 38, 43, 649
 time of arrival, 675
- Weapons:
 control of, 17
 kill radius, 8, 47
 miss distance, 522
- Weather:
 all-weather operations, 597
 for ATM, 642, 672–673, 678, 682
 briefing, 656
 cyclonic winds, 12
 forecast, 598, 672, 680
 GPS, 210
 IMC, 9
 landing, 597–598
 runway visual range,
 star visibility, 562
See also Ceiling; Lightning

- Weather radar, 540–545
 - history, 503
 - precipitation effect, 542
 - See also* Display
- Week number, GPS, 222
- Weight of receivers:
 - direction finder, 117
 - DME, 131
 - Doppler radar, 490
 - GPS antenna, 245
 - inertial navigator, 317, 349
 - marker beacon, 122
 - mechanical gyroscope, 345
 - optical gyroscope, 340
 - radar altimeter, 491, 493
 - Tacan, 136
 - VOR, 126
- Weighting factors, *see* Filter
- Westinghouse Corporation, 637
- WGS, *see* World Geodetic System
- Whisky compass, 440
- Wide-area DGPS, *see* WAAS
- Wilcox Corporation, 614, 615
- Wild point, 48
- Wind:
 - aircraft carrier, 631
 - cross-wind landing, 603–604
 - dead reckoning, 30
 - Doppler radar, 484
 - in-flight calculation, 408
 - during landing, 599, 603
- LLWAS, 673
 - measured by radar, 540
 - shear, 16, 418–420, 540, 543, 673
 - steering, 41
- Window:
 - atmospheric, 109
 - distortion, 577
 - optical, 552, 577
 - radar PVU, 525
- WMM, *World Magnetic Model*, 437
- WMS, *wide-area master station*, 269
- Wobbling modulation, 495
- World Geodetic System:
 - dimensions, 25, 224
 - gravitation, 187
- World War II:
 - navigation, 12
 - radar, 503, 507
- WRS, *wide-area reference station*, 269
- WWV radio, 575
- WWV-H radio, 575
- X-15 air data, 421
- X-band, 101, 517, 538, 542, 550, 634
- Yaw damper, 400
- Z-beacon, 12
- Z-count, 204
- Zero crossings, Loran, 141
- Zonal harmonics, *see* Spherical harmonics